



# Allied Telesis AT-DMC100/ST-50 convertidor de medio 100 Mbit/s 1310 nm Multimodo



Marca : Allied Telesis      Código del producto: 990-004824-50

Nombre del producto : AT-DMC100/ST-50

Allied Telesis AT-DMC100/ST-50. Rango máximo de transferencia de datos: 100 Mbit/s, Interfaz de convertidor de entrada: 100Base-TX, Interfaz de convertidor de salida: 100Base-FX. Distancia de transferencia máxima: 2000 m, Longitud de onda: 1310 nm, Estructura de modo de fibra: Multimodo. Conector fibra óptica: ST. Ancho: 31,8 mm, Profundidad: 91,4 mm, Altura: 21,6 mm

| Conexión                                               |                         | Características                                   |             |
|--------------------------------------------------------|-------------------------|---------------------------------------------------|-------------|
| Rango máximo de transferencia de datos *               | 100 Mbit/s              | Interno *                                         | ✗           |
| Interfaz de convertidor de entrada                     | 100Base-TX              | Puertos e Interfaces                              |             |
| Interfaz de convertidor de salida                      | 100Base-FX              | Conector fibra óptica *                           | ST          |
| Ethernet LAN, velocidad de transferencia de datos      | 100 Mbit/s              | Enchufe de entrada de CC                          | ✓           |
| Velocidad de redireccionamiento de paquetes (10 Mbps)  | 1488000 pps             | Peso y dimensiones                                |             |
| Velocidad de redireccionamiento de paquetes (100 Mbps) | 148800 pps              | Ancho                                             | 31,8 mm     |
| Velocidad de redireccionamiento de paquetes (1 Gbps)   | 14880 pps               | Profundidad                                       | 91,4 mm     |
| Auto MDI / MDI-X                                       | ✓                       | Altura                                            | 21,6 mm     |
| Limitar tasa                                           | ✓                       | Peso                                              | 113,39 g    |
| Sistema de dúplex                                      | Completo, Semi (dúplex) | Condiciones ambientales                           |             |
| Tipos de cable soportados                              | Fibra                   | Intervalo de temperatura operativa                | 0 - 40 °C   |
| Desempeño                                              |                         | Intervalo de temperatura de almacenaje            | -15 - 65 °C |
| Distancia de transferencia máxima *                    | 2000 m                  | Intervalo de humedad relativa para funcionamiento | 5 - 95%     |
| Longitud de onda *                                     | 1310 nm                 | Intervalo de humedad relativa durante almacenaje  | 5 - 95%     |
| Estructura de modo de fibra                            | Multimodo               | Altitud de funcionamiento                         | 0 - 3048 m  |
|                                                        |                         | Contenido del embalaje                            |             |
|                                                        |                         | Adaptador AC incluido                             | ✓           |
|                                                        |                         | Datos logísticos                                  |             |
|                                                        |                         | Código de Sistema de Armomización (SA)            | 85176990    |



0767035206653



767035206653

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.