



APC BV650I sistema de alimentación ininterrumpida (UPS) Línea interactiva 0,65 kVA 375 W 1 salidas AC



Marca : APC

Código del producto: BV650I

Nombre del producto : BV650I


APC BV650I. Topología UPS: Línea interactiva, Capacidad de potencia de salida (VA): 0,65 kVA, Potencia de salida: 375 W. Tipo de salida AC: C13 acoplador, Cantidad de salidas AC: 1 salidas AC. Vida útil de la batería (máx.): 5 año(s). Color del producto: Negro, Longitud de cable: 1,52 m. Certificados de conformidad: RoHS, Certificación: CE



Características		Batería	
Topología UPS *	Línea interactiva	Vida útil de la batería (máx.)	5 año(s)
Capacidad de potencia de salida (VA) *	0,65 kVA	Diseño	
Potencia de salida *	375 W	Longitud de cable	1,52 m
Forma de onda *	Seno	Color del producto *	Negro
Voltaje de entrada de operación (min) *	170 V	Condiciones ambientales	
Voltaje de entrada de operación (max) *	280 V	Intervalo de temperatura operativa	0 - 40 °C
Frecuencia de entrada *	50/60 Hz	Intervalo de humedad relativa para funcionamiento	0 - 90%
Voltaje de operación de salida (min)	0 V	Aprobaciones regulatoras	
Voltaje de operación de salida (max)	0 V	Certificados de conformidad	RoHS
Regulación de la frecuencia de salida	50/60 Hz	Certificación	CE
Índice de aumento de energía	156 J	Contenido del embalaje	
Tiempo de transferencia (de modo Línea a modo Batería)	6 ms	Incluye tarjeta de gestión	✗
Nivel de ruido	40 dB	Peso y dimensiones	
Protección de sobrecarga	✓	Ancho	160 mm
Alarma(s) audibles	✓	Profundidad	305 mm
Modos de alarma audibles	Suena una alarma cuando cambia a la batería, Alarma de batería baja, Alarma de sobrecarga	Altura	92 mm
Puertos e Interfaces		Peso	4,5 kg
Tipo de salida AC	C13 acoplador	Empaquetado	
Cantidad de salidas AC	1 salidas AC	Ancho del paquete	143 mm
SmartSlot	✗	Profundidad del paquete	373 mm
Puerto SmartConnect	✗	Altura del paquete	237 mm
		Peso del paquete	4,8 kg
		Datos logísticos	
		Código de Sistema de Armomización (SA)	85078000
		Otras características	
		Tipo de batería	leakproof
		Voltaje de salida	230 V



0731304338307



731304338307

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.