

CyberPower Systems CyberPower CP1200EIPFCRM2U, Line-Interactive, 1.2 kVA, 720 W, Pure sine, 169 V, 271 V

720 Watt - 1200 VA - USB - serial - 8 - aktive PFC - 2U - Schwarz



Group	Power Supply
Manufacturer	CyberPower Systems
Manufacturer item no.	CP1200EIPFCRM2U
EAN/UPC	4711027798233

Description

CyberPower CP1200EIPFCRM2U. UPS topology: Line-Interactive, Output power capacity: 1.2 kVA, Output power: 720 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 3.4 min, Typical backup time at half load: 11.6 min. Form factor: Rackmount, Product colour: Black, Housing material: Metal. Compliance certificates: CE, RoHS

Main features

	General
UPS topology	Line-Interactive
Output power	720 W
Output power capacity	1.2 kVA
AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	8 AC outlet(s)
Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	3.4 min
Typical backup time at half load	11.6 min
Form factor	Rackmount
Product colour	Black
Housing material	Metal
Compliance certificates	CE, RoHS

Extended details

	Features
UPS topology	Line-Interactive
Output power capacity	1.2 kVA
Output power	720 W

Waveform	Pure sine
Input operation voltage (min)	169 V
Input operation voltage (max)	271 V
Input frequency	50/60 Hz
Output frequency	50/60 Hz
Output frequency regulation	1 Hz
Automatic Voltage Regulation (AVR)	Yes
Heat dissipation	17.1 BTU/h
Power factor	0.6
Power Factor Correction (PFC) type	Active
ECO mode	Yes
EMI/RFI noise filtering	Yes
Surge protection	Yes
Power protection features	Over voltage, Overload
Power source type	AC
Detachable power cord	Yes

Design

Form factor	Rackmount
Product colour	Black
Housing material	Metal
Rack capacity	2U
Cooling type	Active
Built-in fan	Yes
Control type	Buttons
Display type	LCD
LED indicators	Yes

Ports & interfaces

AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	8 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
Serial ports quantity	1
RS-232 ports	1

Ethernet LAN (RJ-45) ports	2
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Number of batteries supported	1
Typical backup time at full load	3.4 min
Typical backup time at half load	11.6 min
Hot-swap battery	Yes
Other features	
Battery type	RBP0181
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 95 %
Weight & dimensions	
Width	433 mm
Depth	274 mm
Height	86 mm
Weight	11.6 kg
Certificates	
Compliance certificates	CE, RoHS