

NETGEAR GS316EPP Gestionado Gigabit Ethernet (10/100/1000) Energía sobre Ethernet (PoE) Negro



Marca : NETGEAR

Código del producto: GS316EPP-100PES

Nombre del producto : GS316EPP

NETGEAR GS316EPP. Tipo de interruptor: Gestionado. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 16. Bidireccional completo (Full duplex). Tabla de direcciones MAC: 4000 entradas, Capacidad de conmutación: 28 Gbit/s. Estándares de red: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x. Energía sobre Ethernet (PoE)

| Características de administración                           |                                                                                | Diseño                                            |             |
|-------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------|-------------|
| Tipo de interruptor *                                       | Gestionado                                                                     | Apilable *                                        | ✗           |
| Calidad de servicio (QoS) soporte                           | ✓                                                                              | Color del producto                                | Negro       |
| Administación basada en web                                 | ✓                                                                              | Indicadores LED                                   | ✓           |
| Puertos e Interfaces                                        |                                                                                | Control de energía                                |             |
| Cantidad de puertos básicos de conmutación RJ-45 Ethernet * | 16                                                                             | Fuente de energía *                               | CC          |
| Puertos tipo básico de conmutación RJ-45 Ethernet *         | Gigabit Ethernet (10/100/1000)                                                 | Fuente de alimentación incluida *                 | ✓           |
| Gigabit Ethernet (cobre), cantidad de puertos               | 16                                                                             | Alimentación a través de Ethernet (PoE)           |             |
| Cantidad de ranuras del módulo SFP                          | 1                                                                              | Energía sobre Ethernet (PoE) *                    | ✓           |
| Conexión                                                    |                                                                                | Cantidad de puertos Power over Ethernet (PoE)     | 15          |
| Estándares de red *                                         | IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x | Potencia a través de Ethernet (PoE) Presupuesto   | 231 W       |
| Bidireccional completo (Full duplex)                        | ✓                                                                              | Condiciones ambientales                           |             |
| Soporte de control de flujo                                 | ✓                                                                              | Intervalo de temperatura operativa                | 0 - 40 °C   |
| Adición de vínculos                                         | ✓                                                                              | Intervalo de temperatura de almacenaje            | -20 - 70 °C |
| Control de transmisión de tormentas                         | ✓                                                                              | Intervalo de humedad relativa para funcionamiento | 0 - 90%     |
| Soporte VLAN                                                | ✓                                                                              | Intervalo de humedad relativa durante almacenaje  | 0 - 95%     |
| Transmisión de datos                                        |                                                                                | Altitud de funcionamiento                         | 0 - 3000 m  |
| Capacidad de conmutación *                                  | 28 Gbit/s                                                                      | Altitud no operativa                              | 0 - 3000 m  |
| Tabla de direcciones MAC *                                  | 4000 entradas                                                                  | Peso y dimensiones                                |             |
| Jumbo Frames, soporte                                       | ✓                                                                              | Ancho                                             | 286 mm      |
| Tramas Jumbo                                                | 10000                                                                          | Profundidad                                       | 102 mm      |
| Seguridad                                                   |                                                                                | Altura                                            | 27 mm       |
| Características de DHCP                                     | DHCP client                                                                    | Peso                                              | 883 g       |
| Lista de Control de Acceso (ACL)                            | ✓                                                                              | Datos logísticos                                  |             |
| Funciones de multidifusión                                  |                                                                                | Código de Sistema de Armomización (SA)            | 85176990    |
| Multidifusión, soporte                                      | ✓                                                                              |                                                   |             |



0606449154405



606449154405



5715063041086

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.