ZYXEL

Zyxel NWA50AX PRO 2400 Mbit/s Blanco Energía sobre Ethernet (PoE)



Marca : Zyxel

Código del producto: NWA50AXPRO-EU0102F

Nombre del producto : NWA50AX PRO

Zyxel NWA50AX PRO. 2,4 GHz, 5 GHz, Rango máximo de transferencia de datos: 2400 Mbit/s. Algoritmos de seguridad soportados: WPA, WPA2, WPA3. Ethernet LAN, velocidad de transferencia de datos: 1000,2500 Mbit/s. Energía sobre Ethernet (PoE). Color del producto: Blanco



Características	
2,4 GHz *	✔
5 GHz *	✔
6 GHz *	✘
Rango máximo de transferencia de datos *	2400 Mbit/s
Velocidad máxima de transferencia de datos (2,4 GHz)	575 Mbit/s
Velocidad máxima de transferencia de datos (5 GHz)	2400 Mbit/s
Ethernet LAN, velocidad de transferencia de datos	1000,2500 Mbit/s
Estándares de red	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
MIMO	✔
Tipo MIMO	Multi User MIMO
Wi-Fi Multimedia (WMM)/(WME)	✔
Soporte VLAN	✔

Seguridad	
Algoritmos de seguridad soportados *	WPA, WPA2, WPA3
MAC, filtro de direcciones	✔

Protocolos	
Protocolos de gestión	SNMP

Características de administración	
Administación basada en web	✔
Firmware actualizable	✔

Puertos e Interfaces	
Ethernet LAN (RJ-45) cantidad de puertos *	1
Enchufe de entrada de CC	✔

Control de energía	
Corriente de entrada	0.3 A
Voltaje de salida	12 V
Corriente de salida	2 A

Diseño	
Ubicación *	Techo
Color del producto *	Blanco
Indicadores LED	✔

Antena	
Tipo de antena *	Interno
Características de la antena	Antena integrada
Ganancia de la antena (max)	4 dBi

Peso y dimensiones	
Ancho	140 mm
Profundidad	140 mm
Altura	37,5 mm
Peso	352 g

Empaquetado	
Ancho del paquete	240 mm
Profundidad del paquete	155 mm
Altura del paquete	60 mm
Peso del paquete	668 g

Contenido del embalaje	
Cantidad por paquete	1 pieza(s)
Adaptador AC incluido	✔
Kit de montaje	✔

Condiciones ambientales	
Intervalo de humedad relativa para funcionamiento	10 - 90%
Intervalo de temperatura operativa	0 - 50 °C

Control de energía	
Energía sobre Ethernet (PoE) *	✔
Voltaje de entrada AC	100 - 240 V
Frecuencia de entrada AC	50/60 Hz

Condiciones ambientales	
Intervalo de temperatura de almacenaje	-40 - 70 °C
Intervalo de humedad relativa durante almacenaje	10 - 90%

4718937630554

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 05-NOV-2026. Prints or copies of Information are only valid on the printed Publication date