

AISENS Cable de Red RJ45 LSZH CPR Dca CAT.7 600 MHZ S/FTP AWG23, Azul, 100 m

Marca : AISENS

Código del producto: A146-0664

Nombre del producto : Cable de Red RJ45 LSZH CPR Dca CAT.7 600 MHZ S/FTP AWG23, Azul, 100 m

- Cable de 4 pares: 4x2xAWG23/1 (Rígido) Diámetro: 0.57 mm
- Este cable Ethernet de gran calidad ha sido diseñado para redes Ethernet de 10/100/1000/1000/10000 Mbit (10 Gigabit/s), es capaz de transferir datos a velocidades de hasta 10 Gbit/s, diez veces más rápido que gigabit Ethernet. Alta velocidad de transmisión mediante una frecuencia de trabajo de hasta 600 MHz
- Cumple las Normativas ISO/IEC 11801:2002 Categoría7/ClaseF, CPR (UE 305/2011) Clase Dca – EN50575:2014+A1:2016, EN 60332-1-2:2004+A1:2015 A11:2016, EN 50399:2011+A1:2016, EN 60754-2:2014, EN 13501-6:2014
- Conductor OFC (Oxygen Free Copper), pureza 99,9% con diámetro AWG23 que garantiza la transferencia de datos
- Libre de halógenos (LSZH o LSOH o LSFH)
- Apto para PoE (Power over Ethernet)

Cable de Red RJ45 LSZH CPR Dca CAT.7 600 MHZ S/FTP AWG23, Azul, 100 m

AISENS Cable de Red RJ45 LSZH CPR Dca CAT.7 600 MHZ S/FTP AWG23, Azul, 100 m:

AISENS® – Bobina cable de red CPR Dca CAT.7 S/FTP PIMF AWG23 100% cobre.



Características		Sostenibilidad	
Color del producto *	Azul	No contiene	Halógeno
Longitud de cable *	100 m	Aprobaciones reguladoras	
Cable estándar *	Cat7	Certificados de conformidad	RoHS
Blindaje de cable *	SF/UTP (S-FTP)	Certificación	CPR Cca-s1a,d1,a1
Conector 1 *	✗	Contenido del embalaje	
Conector 2 *	✗	Cantidad por paquete	1 pieza(s)
Género del conector 1 *	✗	Empaquetado	
Género del conector 2 *	✗	Ancho del paquete	280 mm
Material de chaqueta	Libre de halógenos (LSZH)	Profundidad del paquete	280 mm
Forma del cable *	Alrededor	Altura del paquete	160 mm
Clase de protección contra el fuego del cable	Cca	Peso del paquete	6,3 kg
Tipo de interfaz ethernet	10 Gigabit Ethernet, Ethernet rápido, Gigabit Ethernet	Volumen del paquete	12544 cm³
AWG calibre del cable	23	Tipo de embalaje	Caja
Velocidad de transferencia de datos	10000 Mbit/s	Datos logísticos	
Frecuencia	600 MHz	Ancho de la caja principal	295 mm
Energía sobre Ethernet (PoE)	✓	Longitud de la caja	295 mm
Condiciones ambientales		Peso del envase completo	12,6 kg
Intervalo de temperatura operativa	-20 - 60 °C	Alto de la caja principal	340 mm
		Cantidad por caja	2 pieza(s)
		Volumen de caja	29588,5 cm³



8436574707793

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.