

MPN: PC-KOE-001W-M

## Power Cord Denmark to Open End 1M White

The PC-KOE-001W-M power cord is suited for montage situations and enables customization of a cable with a straight male type K connector on one end, and an open end on the other.

This type H05VV-F power cable is wrapped in a PVC jacket and features 3 cores consisting of 32 conductors each. The cable core size is 1mm<sup>2</sup> and its supported input voltage is 250V, and input current is 16A.

Type K connectors are most often used in Denmark and Greenland.



### Especificaciones

<b>Features</b>	<b>Apto para su uso en el país / ubicación</b>	Denmark
	<b>Certificación</b>	VDE, Demko
	<b>Color producto</b>	White
	<b>Conector 1</b>	Power plug type K
	<b>Conector 1 bloqueable</b>	No
	<b>Conector 1 género</b>	Male
	<b>Conector 2 género</b>	Female
	<b>Factor forma conector 1</b>	Straight
	<b>Longitud del cable</b>	1 m
	<b>Material conductor</b>	Copper
	<b>Material cubierta</b>	Polyvinyl chloride (PVC)
	<b>Número de conductores</b>	32
	<b>Número de núcleos de cable</b>	3
	<b>Plug and play</b>	No
	<b>Protección contra sobre-tensión</b>	No
	<b>Tamaño del núcleo</b>	1 mm <sup>2</sup>
	<b>Tipo de cable</b>	H05VV-F
<b>Operational conditions</b>	<b>Temperatura de almacenamiento (T-T)</b>	-20 - 70 °C
	<b>Temperatura de funcionamiento (T-T)</b>	-15 - 60 °C
<b>Packaging data</b>	<b>Cantidad por pack</b>	1 pieza(s)
<b>Power</b>	<b>Corriente de entrada</b>	16 A
	<b>Voltaje de entrada</b>	250 V
<b>Sustainability</b>	<b>Certificados de sostenibilidad</b>	RoHS, REACH, Low Voltage Directive (LVD)

<b>Sustainability</b>	<b>Conformidad sostenibilidad</b>	Yes
<b>Technical details</b>	<b>Compliance certificates</b>	RoHS, REACH, Low Voltage Directive (LVD)
<b>Vendor information</b>	<b>Brand Name</b>	ProXtend
	<b>Warranty</b>	30 Año/s