



## Product Feature

- Industrial level DID LCD panel, suitable for extensive 7×24 continuous works.
- Physical resolution of 1920×1080.
- 5ms fast response time, no image ghosting.
- Adapt newest 3D digital filtering and 3D digital noise reduction technology.
- Picture fast response; 178° wide viewing angle; Ensure that the image display is not deformed.
- High fidelity digital processing, brilliant and vivid video.
- Built-in speaker.
- Humanize Menu;

## DNle digital image processing

Dynamic optimization



Natural color



Contrast enhancement



Detail enhancement



## DISPLAY CHARACTERISTICS

|                          |                                            |
|--------------------------|--------------------------------------------|
| Mode Name                | 0070-24124-W-TOUCH                         |
| Screen Size              | 24"                                        |
| Active Display Area (mm) | 521.28mm(W)×293.22mm(H)                    |
| Display Mode             | 16:9                                       |
| LED Type                 | TFT-LED                                    |
| Resolution               | 1920 × 1080                                |
| Display Color            | 16.7M                                      |
| Pixel Pitch(mm)          | 0.630(H)×0.630(V)                          |
| Brightness(nits)         | 350cd/m2 (With Brightness auto adjustment) |
| Contrast Ratio           | 1000:1                                     |
| Viewing Angle            | 178(H) /178(V)                             |
| Response Time            | 5ms                                        |
| Backlight                | LED                                        |

## INPUT&OUTPUT

|                   |                     |
|-------------------|---------------------|
| HDMI 2.0          | 1                   |
| VGA               | 1                   |
| Speaker           | YES                 |
| Remote controller | YES                 |
| USB               | 1(Touch Screen use) |

## Protection

|                       |                                            |
|-----------------------|--------------------------------------------|
| Waterproof            | IP 67 at front case and IP 22 at back case |
| Vandal-proof          | Support                                    |
| 3D comb filter        | YES                                        |
| Video Noise Reduction | YES                                        |

## POWER&Mount Way

|                     |                                    |
|---------------------|------------------------------------|
| Power               | AC100-240V ,50/60Hz                |
| Working Temperature | -30 to +85                         |
| Power Consumption   | <30W                               |
| Menu                | English(other languages supported) |
| Mounting/Weight     | Stand mount, VESA mount/10kg       |
| MTBF                | 50000Hours                         |

## ACCESSORIES

|                      |                                                       |
|----------------------|-------------------------------------------------------|
| INCLUDED ACCESSORIES | Industrial PSU,Screw, Cable holder, Quick start guide |
|----------------------|-------------------------------------------------------|