

MPN: 5UTP-100

# CAT5e U/UTP CU PVC Ethernet Cable

## Orange 10m

Designed to last a lifetime, the ProXtend CAT5e U/UTP copper ethernet cables are reinforced with strain relief and snagless latch protection.

Available in both copper and copper-clad aluminum variants, as well as a variety of color, and length options, ProXtend is your one stop shop for ethernet cables ensuring that you are always able to find a cable that best suits your network connection requirements.



## Especificaciones

|                               |  |                          |
|-------------------------------|--|--------------------------|
| <b>Certificates</b>           | <b>Certificación</b>                           | REACH                    |
| <b>Features</b>               | <b>Blindaje de cable</b>                       | U/UTP (UTP)              |
|                               | <b>Cable estándar</b>                          | Cat5e                    |
|                               | <b>Color producto</b>                          | Orange                   |
|                               | <b>Conector 1</b>                              | RJ45                     |
|                               | <b>Conector 1 género</b>                       | Male                     |
|                               | <b>Conector 2</b>                              | RJ45                     |
|                               | <b>Conector 2 género</b>                       | Male                     |
|                               | <b>Estándares de red</b>                       | IEEE 802.3at             |
|                               | <b>Longitud del cable</b>                      | 10 m                     |
|                               | <b>Material conductor</b>                      | Copper                   |
|                               | <b>Material cubierta</b>                       | Polyvinyl chloride (PVC) |
|                               | <b>Plug and play</b>                           | Yes                      |
|                               | <b>Revestimiento de contactos del conector</b> | Gold                     |
|                               | <b>Tamaño de cable AWG</b>                     | 24                       |
|                               | <b>Tecnología de cableado</b>                  | 10/100/1000Base-T(X)     |
|                               | <b>Tipo de conductor</b>                       | Stranded                 |
|                               | <b>Velocidad de transferencia de datos</b>     | 1000 Mbit/s              |
| <b>Operational conditions</b> | <b>Temperatura de almacenamiento (T-T)</b>     | -15 - 60 °C              |
|                               | <b>Temperatura de funcionamiento (T-T)</b>     | -10 - 60 °C              |
| <b>Packaging data</b>         | <b>Cantidad por pack</b>                       | 1 pieza(s)               |
|                               | <b>Manual</b>                                  | No                       |
| <b>Technical details</b>      | <b>Certificados de sostenibilidad</b>          | RoHS                     |

|                                |                                |          |
|--------------------------------|--------------------------------|----------|
| <b>Technical details</b>       | <b>Compliance certificates</b> | RoHS     |
| <b>Vendor information</b>      | <b>Brand Name</b>              | ProXtend |
|                                | <b>Warranty</b>                | 30 Año/s |
| <b>Weight &amp; dimensions</b> | <b>Díámetro exterior</b>       | 5,4 mm   |

## Otras imágenes

