

D-Link DMS-1016 No administrado L2+ 2.5G Ethernet (100/1000/2500) Negro



Marca : D-Link

Código del producto: DMS-1016/E

Nombre del producto : DMS-1016

- 16-port 2.5GE connectivity for high performance networking
 - Plug and Play simplicity for easy installation
 - Fanless design for enhanced reliability and silent performance
 - Durable rackmount metal housing enhances product durability
 - IGMP snooping for optimized bandwidth utilization
 - Auto MDI/MDI-X crossover on all ports simplifies setup
 - IEEE 802.3x flow control prevents packet loss
 - Quality of Service (QoS) ensures uninterrupted connectivity
 - IEEE 802.3az reduces power consumption and operating cost
- 16 x 10M/100M/1G/2.5G, 80 Gbps, 59.52 Mbps, 440 x 250 x 44 mm, 2.932 kg

Características de administración		Desempeño	
Tipo de interruptor *	No administrado	Tiempo medio entre fallos	800034,25 h
Capa del interruptor	L2+	Control de energía	
Calidad de servicio (QoS) soporte	✓	Fuente de energía *	CC
Clasificación del tráfico	✓	Fuente de alimentación incluida *	✓
Puertos e Interfaces		Voltaje de entrada DC	12 V
Cantidad de puertos básicos de conmutación RJ-45 Ethernet *	16	Corriente de entrada	5.4 A
Puertos tipo básico de conmutación RJ-45 Ethernet *	2.5G Ethernet (100/1000/2500)	Consumo de energía (max)	19,135 W
Conector eléctrico	Toma de entrada de CC	Alimentación a través de Ethernet (PoE)	
Conexión		Energía sobre Ethernet (PoE) *	✗
Estándares de red *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x	Condiciones ambientales	
		Intervalo de temperatura operativa	-5 - 50 °C
Soporte 10G *	✗	Intervalo de temperatura de almacenaje	-20 - 70 °C
Auto MDI / MDI-X	✓	Intervalo de humedad relativa para funcionamiento	10 - 90%
Ethernet LAN, velocidad de transferencia de datos	10,100,1000,2500 Mbit/s	Intervalo de humedad relativa durante almacenaje	0 - 95%
Transmisión de datos		Disipación del calor	62,29 BTU/h
Capacidad de conmutación *	80 Gbit/s	Peso y dimensiones	
Tasa de reenvío	59,52 Mpps	Ancho	440 mm
Tabla de direcciones MAC *	16000 entradas	Profundidad	250 mm
Guardar y remitir	✓	Altura	44 mm
Jumbo Frames, soporte	✓	Peso	2,93 kg
Tramas Jumbo	12288	Contenido del embalaje	
Diseño		Guía de configuración rápida	✓
Apilable *	✓	Aprobaciones regulatoras	
Color del producto	Negro	Certificación	LVD; CE Class A, FCC Class A
Indicadores LED	✓		



0790069477027



790069477027

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.