

MPN: V-5UTP-20B

## CAT5e U/UTP CCA PVC Ethernet Cable Black 20m

The ProXtend CAT5e U/UTP CCA ethernet cables are produced with a copper-clad aluminum strands and an AWG of 26 to create a cost-effective product.

The cable is reinforced with strain relief for increased durability and latch protection allowing for secure installation.

Supporting a variety of cable standards, lengths and shieldings, ProXtend is your one stop shop for ethernet cables ensuring that you are always able to find a cable that best suits your network connection requirements.



### Especificaciones

|                        |                                         |                             |
|------------------------|-----------------------------------------|-----------------------------|
| Certificates           | Certificación                           | REACH, CE                   |
| Features               | Blindaje de cable                       | U/UTP (UTP)                 |
|                        | Cable estándar                          | Cat5e                       |
|                        | Color producto                          | Black                       |
|                        | Conector 1                              | RJ45                        |
|                        | Conector 2                              | RJ45                        |
|                        | Género del conector                     | Male/Male                   |
|                        | Longitud del cable                      | 20 m                        |
|                        | Material conductor                      | Copper-Clad Aluminium (CCA) |
|                        | Material cubierta                       | Polyvinyl chloride (PVC)    |
|                        | Plug and play                           | Yes                         |
|                        | Revestimiento de contactos del conector | Gold                        |
|                        | Tamaño de cable AWG                     | 26                          |
|                        | Tecnología de cableado                  | 10/100/1000Base-T(X)        |
|                        | Tipo de conductor                       | Stranded                    |
|                        | Velocidad de transferencia de datos     | 1000 Mbit/s                 |
| Operational conditions | Temperatura de almacenamiento (T-T)     | -15 - 60 °C                 |
|                        | Temperatura de funcionamiento (T-T)     | -10 - 60 °C                 |
| Packaging data         | Cantidad por pack                       | 1 pieza(s)                  |
|                        | Manual                                  | No                          |
| Technical details      | Certificados de sostenibilidad          | RoHS                        |
|                        | Compliance certificates                 | RoHS                        |

**Vendor information**

|                   |          |
|-------------------|----------|
| <b>Brand Name</b> | ProXtend |
| <b>Warranty</b>   | 30 Año/s |

**Weight & dimensions**

|                          |        |
|--------------------------|--------|
| <b>Diámetro exterior</b> | 4,5 mm |
|--------------------------|--------|

## Otras imágenes

