



Epson EB-L530U - 3LCD projector

5200 lumens (white) - 5200 lumens (colour) - WUXGA (1920 x 1200) - 16:10 - 1080p - 802.11a/b/g/n/ac wireless / LAN/ Miracast - white

Group	Projectors
Manufacturer	Epson
Manufacturer item no.	V11HA27040
EAN/UPC	8715946695334

Description

As the market leader in 3LCD technology, Epson continues to improve its high-brightness laser projectors with even smaller and more compact display solutions. EB-L530U delivers even more effective, practical and creative display applications across a number of different industries.

Main features

Product Description	Epson EB-L530U - 3LCD projector - 802.11a/b/g/n/ac wireless / LAN/ Miracast - white
Device Type	3LCD projector - 1080p
Colour	White
Brightness (White)	5200 lumens
Brightness (Colour)	5200 lumens
Contrast Ratio	2500000:1 (dynamic)
Resolution	WUXGA (1920 x 1200)
Native Aspect Ratio	16:10
Colour Support	1.07 billion colours
Lens Shift Direction	Horizontal, vertical
Bulb type	Laser
Bulb life cycle	Up to 20000 hour(s) - normal mode Up to 30000 hour(s) - economic mode
Video Input	IEEE 802.11a/b/g/n/ac wireless / LAN/ Miracast
Speakers	Speaker(s) - integrated
Power	AC 120/230 V (50 - 60 Hz)
Power Consumption Operational	293 Watt
Dimensions (WxDxH)	44 cm x 33.9 cm x 13.6 cm
Weight	8.2 kg

Extended details

General



Device Type	3LCD projector - 1080p
Networking	802.11a/b/g/n/ac, Ethernet
Enclosure Colour	White
Projector	
Brightness (White)	5200 lumens
Brightness (Colour)	5200 lumens
Brightness (Reduced)	3640 lumens
Contrast Ratio	2500000:1 (dynamic)
Image Size	127 cm - 1270 cm
Projection Distance	1.44 m - 23.84 m
Throw Ratio	1.35 - 2.2:1
Resolution	WUXGA - WUXGA (1920 x 1200)
Native Aspect Ratio	16:10
Colour Support	1.07 billion colours
Bulb type	Laser
Bulb life cycle	Up to 20000 hour(s) - normal mode Up to 30000 hour(s) - economic mode
Features	EPSON Quick Corner, Edge blending, EPSON 3LCD technology, Web Remote Control, DICOM Simulation Mode, Direct Power On, Direct Power Off, Dynamic Mode, full 10-bit image processing, auto power on, document camera compatible, Cinema Mode
Lens	
Focus Type	Manual
Lens Aperture	F/1.5 -1.7
Zoom Type	Manual
Zoom Factor	1.6x
Keystone Correction Direction	Horizontal, vertical
Vertical Keystone Correction	-30 / +30
Horizontal Keystone Correction	-30 / +30
Lens Shift Type	Manual
Lens Shift Direction	Horizontal, vertical
Vertical Lens Shift	50% / 50%
Horizontal Lens Shift	20% / 20%
Video Input	
Video Interfaces	VGA, HDMI
LAN and Wireless Image Transferring Protocols	IEEE 802.11b, IEEE 802.11g, wired LAN, IEEE 802.11a, IEEE 802.11n, Miracast, IEEE 802.11ac
Speakers	
Type	Integrated
Sound Output Mode	Mono
Output Power / Channel	10 Watt
Speakers	1 x mixed channel
Expansion / Connectivity	
Interfaces	2 x USB 2.0 - 4 pin USB Type A 1 x USB 2.0 - 4 pin USB Type B (management) 1 x serial RS-232C 1 x network - RJ-45 2 x VGA input - 15 pin HD D-Sub

(HD-15) | 1 x VGA output - 15 pin HD D-Sub (HD-15) | 2 x HDMI - 19 pin HDMI Type A | 1 x HDBaseT - RJ-45 | 1 x audio line-out - mini-phone stereo 3.5 mm | 2 x audio line-in - mini-phone stereo 3.5 mm | 1 x HDMI output - 19 pin HDMI Type A

Miscellaneous

Included Accessories	Cable cover, remote control, battery for remote control
Security Features	Security lock slot (cable lock sold separately), password protection, control panel lock, Wireless LAN Lock, security cable hole
Security Slot Type	Kensington security slot

Power

Power Source	AC
Voltage Required	AC 120/230 V (50 - 60 Hz)
Power Consumption Operational	293 Watt
Power Consumption Stand by	0.3 Watt

Dimensions & Weight

Width	44 cm
Depth	33.9 cm
Height	13.6 cm
Weight	8.2 kg

Dimensions & Weight (Shipping)

Shipping Width	53.1 cm
Shipping Depth	56.4 cm
Shipping Height	20.3 cm
Shipping Weight	11.6 kg

Environmental Parameters

Humidity Range Operating	20 - 80%
Sound Emission	31 dBA
Sound Emission (Economic Mode)	23 dBA