USB 20 Gbps M.2 Docking Station for 2 x M.2 NVMe PCIe SSD with Clone function

Description

This M.2 docking station by Delock enables the installation of **two M.2 PCIe NVMe SSDs** and it can be connected via USB to the PC or laptop.

M.2 PCIe SSD clone function

The **clone function** enables to copy the content of one SSD to another without using a PC.

Ideal test equipment

The memory is simply plugged into the robust housing and can be used immediately. **No screws, tools or accessories** are required, which means that the SSD can be changed quickly.



Item no. 64364

EAN: 4043619643646

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
  1 x USB 20 Gbps USB Type-C™ female
  2 x M.2 key M slot
  1 x USB Type-C™ female (power supply)
- Chipset: JMicron JMS586U
- Supports M.2 modules with key M or key B+M based on PCIe (NVMe)
- Supports NVM Express (NVMe)
- Data transfer rate up to 20 Gbps
- Supports UASP
- Supports TRIM
- LED indicator for power, access and copy status
- Function key:
  1 x Clone button
  1 x On / Off switch
- Bootable
- Colour: black
- Cable length: ca. 25 cm
- Dimensions (LxWxH): ca. 75 x 75 x 16 mm
- Hot Plug, Plug & Play

Power supply specification

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

- Power supply type: Euro wall power plug
- Model identifier: FJ-SW618SE
- Input voltage: 100 - 240 V
- Input AC frequency: 50 / 60 Hz
- Input current: 0.6 A
- Output voltage / Output current / Output power: 5.0 V / 3.0 A / 15.0 W
- Average active efficiency: 82.5 %
- Efficiency at low load (10 %): 81.1 %
- No-load power consumption: 0.05 W

System requirements

- Android 14.0 or above
- Chrome OS
- Linux Kernel 6.5 or above
- Mac OS 14.5 or above
- Windows 10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- Surface Pro 7
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3, Thunderbolt™ 4 or Thunderbolt™ 5 port

Package content

- M.2 docking station
- External power supply
- Cable USB-C™ male to USB Type-A male, length ca. 80 cm (power supply)
- User manual

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Images











Allgemein

Funktion:	**Netzteilspezifikation** Hot Plug Plug & Play Bootfähig
Spezifikation:	**Netzteilspezifikation** NVM Express (NVMe)
Unterstütztes Betriebssystem:	**Netzteilspezifikation** Chrome OS Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit iPad Pro (3. Generation) oder höher iPad Air (4. Generation) oder höher Windows 11 Android 14.0 oder höher Linux Kernel 6.5 oder höher Mac OS 14.5 oder höher
LED Anzeige:	**Netzteilspezifikation** Power, Zugriff und Kopierstatus
Unterstütztes Modul:	**Netzteilspezifikation** M.2 Module mit Key M oder Key B+M auf PCIe (NVMe) Basis

Schnittstelle

Anschluss:	**Netzteilspezifikation** 1 x USB 20 Gbps USB Type-C™ Buchse 1 x USB Type-C™ Buchse (Stromversorgung) 2 x M.2 Key M Slot

Technische Eigenschaften

Chipsatz:	**Netzteilspezifikation** JMicron JMS586U
Datentransferrate:	**Netzteilspezifikation** bis zu 20 Gbps

Physikalische Eigenschaften

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Kabellänge:	**Netzteilspezifikation** 25 cm
Länge:	**Netzteilspezifikation** 75 mm
Breite:	**Netzteilspezifikation** 75 mm
Höhe:	**Netzteilspezifikation** 16 mm
Farbe:	**Netzteilspezifikation** schwarz

Netzteil

Netzteil Typ:	**Netzteilspezifikation** Euro-Steckernetzteil
Modellkennung:	**Netzteilspezifikation** FJ-SW618SE
Eingangsspannung:	**Netzteilspezifikation** 100 - 240 V
Eingangswechselstromfrequenz:	**Netzteilspezifikation** 50 / 60 Hz
Eingangsstrom:	**Netzteilspezifikation** 0,6 A
Ausgangsspannung / Ausgangsstrom / Ausgangsleistung:	**Netzteilspezifikation** 5,0 V / 3,0 A / 15,0 W
Durchschnittliche Effizienz im Betrieb:	**Netzteilspezifikation** 82,5 %
Effizienz bei geringer Last (10 %):	**Netzteilspezifikation** 81,1 %
Leistungsaufnahme bei Nulllast:	**Netzteilspezifikation** 0,05 W

Manufacturer information

Street	Beeskowdamm 13/15

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de



All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**