

ZYXEL


Zyxel NWA50BE PRO 5764 Mbit/s Blanco Energía sobre Ethernet (PoE)

Marca : Zyxel

Código del producto: NWA50BEPRO-EU0102F

Nombre del producto : NWA50BE PRO

Zyxel NWA50BE PRO. 2,4 GHz, 5 GHz, 6 GHz, Rango máximo de transferencia de datos: 5764 Mbit/s. Algoritmos de seguridad soportados: WPA, WPA2, WPA3. Ethernet LAN, velocidad de transferencia de datos: 1000,2500 Mbit/s. Energía sobre Ethernet (PoE). Color del producto: Blanco



Características		Control de energía	
2,4 GHz *	✓	Voltaje de entrada AC	100 - 240 V
5 GHz *	✓	Frecuencia de entrada AC	50/60 Hz
6 GHz *	✓	Rango de voltaje DC	12 V
Rango máximo de transferencia de datos *	5764 Mbit/s	Corriente de entrada	0.3 A
Velocidad máxima de transferencia de datos (2,4 GHz)	688 Mbit/s	Corriente de salida	1,5 A
Velocidad máxima de transferencia de datos (5 GHz)	4324 Mbit/s	Diseño	
Velocidad máxima de transferencia de datos (6 GHz)	5764 Mbit/s	Ubicación *	Techo
Ethernet LAN, velocidad de transferencia de datos	1000,2500 Mbit/s	Color del producto *	Blanco
Estándares de red	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11k, IEEE 802.11n, IEEE 802.11r, IEEE 802.11v, IEEE 802.3at, IEEE 802.3bt	Antena	
MIMO	✓	Tipo de antena *	Interno
Tipo MIMO	Multi User MIMO	Ganancia de la antena (max)	3 dBi
Wi-Fi Multimedia (WMM)/(WME)	✓	Peso y dimensiones	
Itinerancia rápida	✓	Ancho	150 mm
Seguridad		Profundidad	150 mm
Algoritmos de seguridad soportados *	WPA, WPA2, WPA3	Altura	35 mm
MAC, filtro de direcciones	✓	Peso	412 g
Sistema automático de distribución inalámbrica (WDS)	✓	Empaquetado	
		Ancho del paquete	244 mm
		Profundidad del paquete	168 mm
		Altura del paquete	60 mm
		Peso del paquete	785 g
		Contenido del embalaje	
		Adaptador AC incluido	✓
		Kit de montaje	✓

Características de administración		Condiciones ambientales	
Administrado a través de la nube	✓	Intervalo de humedad relativa para funcionamiento	10 - 95%
Puertos e Interfaces		Intervalo de temperatura operativa	0 - 50 °C
Ethernet LAN (RJ-45) cantidad de puertos *	1	Intervalo de temperatura de almacenaje	-40 - 70 °C
Enchufe de entrada de CC	✓	Intervalo de humedad relativa durante almacenaje	10 - 90%
Control de energía			
Energía sobre Ethernet (PoE) *	✓		



4718937649013

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.