



## Equip 128363 Cable USB 3.2 Gen 1 C a A, M/M , 1,0m, 5Gbps, Blanco

**Marca :** Equip

**Código del producto:** 128363

**Nombre del producto :** 128363 Cable USB 3.2 Gen 1 C a A, M/M , 1,0m, 5Gbps, Blanco

- "USB 3.2 Gen 1
  - USB-C Macho
  - USB-A Macho
  - Niquelado
  - Velocidad de transferencia de datos de 5 Gbps
  - Corriente de salida de hasta 3A
  - Cubierta PVC
  - Doble apantallamiento para una transmisión de datos sin errores"
- Cable USB 3.2 Gen 1 C a A, M/M , 1,0m, 5Gbps, Blanco

**Equip 128363 Cable USB 3.2 Gen 1 C a A, M/M , 1,0m, 5Gbps, Blanco:**

"El cable de carga USB-C a USB-A equip® te permite cargar tu dispositivo USB-C y sincronizar tus fotos, música y datos con tu portátil. Disfruta de velocidades de transferencia de hasta 5 Gbps, hasta 10 veces más rápidas que USB 2.0 (480 Mbps).

Además, el cable también admite hasta 3 amperios de potencia de salida para cargar dispositivos USB-C"

Equip 128363 Cable USB 3.2 Gen 1 C a A, M/M , 1,0m, 5Gbps, Blanco. Longitud de cable: 1 m. Conector 1: USB A, Conector 2: USB C, Versión USB: USB 3.2 Gen 1 (3.1 Gen 1), Tasa de transferencia (máx): 5 Gbit/s, Contactos del conector chapado: Níquel, Color del producto: Blanco, Magnéticamente protegida

| Características                        |                             | Características                        |            |
|----------------------------------------|-----------------------------|----------------------------------------|------------|
| Versión USB *                          | USB 3.2 Gen 1 (3.1 Gen 1)   | Color del producto *                   | Blanco     |
| Conector 1 *                           | USB A                       | <b>Control de energía</b>              |            |
| Conector 2 *                           | USB C                       | Voltaje de salida                      | 5 V        |
| Género del conector 1 *                | Macho                       | Corriente de salida (máx.)             | 3 A        |
| Género del conector 2 *                | Macho                       | <b>Peso y dimensiones</b>              |            |
| Factor de forma de conector 1          | Derecho                     | Longitud de cable *                    | 1 m        |
| Factor de forma de conector 2          | Derecho                     | Diámetro de cable                      | 4,5 mm     |
| Contactos del conector chapado         | Níquel                      | Peso                                   | 48 g       |
| Magnéticamente protegida               | ✓                           | <b>Empaquetado</b>                     |            |
| Material del forro del cable           | Cloruro de polivinilo (PVC) | Tipo de embalaje                       | Bolsa      |
| Material del conductor                 | Cobre                       | Ancho del paquete                      | 175 mm     |
| Número de capas de blindaje            | 2                           | Profundidad del paquete                | 0,1 mm     |
| Rango máximo de transferencia de datos | 5000 Mbit/s                 | Altura del paquete                     | 275 mm     |
| Tasa de transferencia (máx)            | 5 Gbit/s                    | Peso del paquete                       | 55 g       |
| Conectar y usar (Plug and Play)        | ✓                           | <b>Contenido del embalaje</b>          |            |
| Consumo de energía                     | 15 W                        | Cantidad por paquete *                 | 1 pieza(s) |
|                                        |                             | <b>Aprobaciones reguladoras</b>        |            |
|                                        |                             | Certificación                          | RoHS       |
|                                        |                             | <b>Datos logísticos</b>                |            |
|                                        |                             | Código de Sistema de Armomización (SA) | 84733080   |
|                                        |                             | País de origen                         | China      |



4015867226803

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.