



LevelOne GVT-2010 convertidor de medio Negro

Marca : LevelOne

Código del producto: GVT-2010

Nombre del producto : GVT-2010

LevelOne GVT-2010. Estándares de red: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, Ethernet LAN, velocidad de transferencia de datos: 10,100,1000 Mbit/s, Tecnología de cableado ethernet de cobre: 100BASE-TX, 1000BASE-T. Tiempo medio entre fallos: 30000 h. Indicadores LED: Actividad, FDX, Enlace, Poder, Color del producto: Negro. Conector fibra óptica: SFP, Tecnología de conectividad: Alámbrico. Voltaje de entrada: 90 - 264 V, Voltaje de salida: 5 V, Corriente de salida: 2 A



Conexión		Control de energía	
Estándares de red	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Voltaje de entrada	90 - 264 V
Ethernet LAN, velocidad de transferencia de datos	10,100,1000 Mbit/s	Voltaje de salida	5 V
Tecnología de cableado ethernet de cobre	100BASE-TX, 1000BASE-T	Corriente de salida	2 A
Tecnología de fibra de cableado ethernet	1000BASE-LX, 1000BASE-SX	Peso y dimensiones	
Jumbo Frames, soporte	✓	Ancho	94 mm
Tramas Jumbo	9000	Profundidad	71 mm
Soporte de control de flujo	✓	Altura	26 mm
Soporte VLAN	✓	Peso	220 g
Auto MDI / MDI-X	✓	Condiciones ambientales	
Guardar y remitir	✓	Intervalo de temperatura operativa	-10 - 60 °C
Sistema de dúplex	Completo, Semi (dúplex)	Intervalo de temperatura de almacenaje	-40 - 85 °C
Desempeño		Intervalo de humedad relativa para funcionamiento	5 - 90%
Tiempo medio entre fallos	30000 h	Contenido del embalaje	
Características		Manual de usuario	✓
Interno *	✗	Empaquetado	
Administración basada en web	✓	Ancho del paquete	120 mm
Indicadores LED	Actividad, FDX, Enlace, Poder	Profundidad del paquete	55 mm
Color del producto	Negro	Altura del paquete	235 mm
Puertos e Interfaces		Peso del paquete	430 g
Tecnología de conectividad	Alámbrico	Aprobaciones reguladoras	
Ethernet LAN (RJ-45) cantidad de puertos	1	Certificados de conformidad	RoHS
Puertos de canal de fibra	1	Certificación	CE, FCC
Conector fibra óptica *	SFP	Datos logísticos	
Alimentación mediante Ethernet Plus (PoE +) Cantidad de puertos	1	Código de Sistema de Armomización (SA)	85176990



4015867195192

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.