



Zebra DS9308-SR Lector de códigos de barras fijo 1D/2D LED Negro

Marca : Zebra

Código del producto: DS9308-SR00004ZCWW

Nombre del producto : DS9308-SR



Zebra DS9308-SR. Tipo: Lector de códigos de barras fijo, Tipo de escaneado: 1D/2D, Tipo de sensor: LED. Tecnología de conectividad: Alámbrico, Interfaz estándar: RS-232, USB. Color del producto: Negro, Código IP (International Protection): IP52, Certificación: EN 50581:2012, RoHS 2011/65/EU (2015/863) - EN 50581:2012, IEC 63000, REACH 1907/2006, IEC 62368-1..... Alimentación: RS-232, USB, Voltaje de entrada: 5.5 V. Peso: 318 g, Ancho: 86 mm, Profundidad: 83 mm

Exploración		Desempeño	
Tipo *	Lector de códigos de barras fijo	Certificación	EN 50581:2012, RoHS 2011/65/EU (2015/863) - EN 50581:2012, IEC 63000, REACH 1907/2006, IEC 62368-1 2nd ed. EN 62368-1:2014/AC:2015, UL/IEC 60950-1, 2nd ed. CAN/CSA C22.2 No.60950-1, 2nd ed. IEC 62471:2006 (Ed.1.0), EN 62471:2008 (LED), FCC 47 CFR Part 15B, ICES-003, EN55032, EN55024, EN55035, VCCI, and SABS
Tipo de escaneado *	1D/2D		
Tipo de sensor *	LED		
Códigos de barras lineales (1D) soportadas *	Codabar, Code 11, Code 128, Code 39, Code 93, EAN-13, GS1 DataBar, MSI, U.P.C.		
2D (matrices y apilados) códigos de barras soportados *	Aztec Code, Códigos de barras compuestos, Matriz de datos, Dot Code A, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39		
Resolución del sensor óptico (An x Al)		Control de energía	
Distancia de trabajo	1280 x 800 Pixeles	Alimentación *	RS-232, USB
Niveles de luz (luz solar directa)	66 cm	Voltaje de entrada	5.5 V
Ángulo de inclinación de lectura	0 - 107700 lx	Peso y dimensiones	
Ángulo de inclinación de lectura		Ancho	86 mm
Puertos e Interfaces		Profundidad	83 mm
Tecnología de conectividad *	Alámbrico	Altura	145 mm
Interfaz estándar *	RS-232, USB	Peso *	318 g
Desempeño		Condiciones ambientales	
Código IP (International Protection)	IP52	Intervalo de temperatura operativa	0 - 50 °C
Color del producto *	Negro	Intervalo de temperatura de almacenaje	-40 - 70 °C
		Intervalo de humedad relativa para funcionamiento	5 - 95%
		Datos logísticos	
		Código de Sistema de Armomización (SA)	84716070



8596375197916

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.