



Lindy 43403 hub de interfaz USB 3.2 Gen 1 (3.1 Gen 1) Type-C 5000 Mbit/s Negro

Marca : Lindy

Código del producto: 43403

Nombre del producto : 43403

Lindy 43403. Interfaz de host: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, Interfaces de concentradores: USB 3.2 Gen 1 (3.1 Gen 1) Type-C. Velocidad de transferencia de datos: 5000 Mbit/s, Color del producto: Negro, Material de la carcasa: Acrilonitrilo butadieno estireno (ABS). Tipo de fuente de alimentación: CC. Peso: 260 g, Dimensiones del conector 1 (anchura x profundidad x altura): 41,1 x 16,5 x 9,5 mm, Dimensiones del conector 2 (anchura x profundidad x altura): 67,5 x 22 x 13,5 mm. Cantidad por paquete: 1 pieza(s), Ancho del paquete: 236 mm, Profundidad del paquete: 255 mm



Puertos e Interfaces		Control de energía	
Interfaz de host *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C	Tipo de fuente de alimentación	CC
Interfaces de concentradores *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C	Peso y dimensiones	
Cantidad de puertos tipo C USB 3.2 Gen 1 (3.1 Gen 1)	1	Peso	260 g
Cantidad de puertos *	2	Dimensiones del conector 1 (anchura x profundidad x altura)	41,1 x 16,5 x 9,5 mm
Tarjeta de lectura integrada	✗	Dimensiones del conector 2 (anchura x profundidad x altura)	67,5 x 22 x 13,5 mm
Enchufe de entrada de CC	✓	Empaquetado	
Características		Cantidad por paquete	1 pieza(s)
Velocidad de transferencia de datos *	5000 Mbit/s	Ancho del paquete	236 mm
Color del producto	Negro	Profundidad del paquete	255 mm
Material de la carcasa	Acrilonitrilo butadieno estireno (ABS)	Peso del paquete	300 g
Indicadores LED	✓	Tipo de embalaje	Bolsa de plástico
Tipo de cable	Cable redondo	Contenido del embalaje	
AWG calibre del cable	26	Manual de usuario	✓
Material del forro del cable	Cloruro de polivinilo (PVC)	Guía de configuración rápida	✓
Longitud de cable	10 m	Condiciones ambientales	
Diámetro de cable	6,5 mm	Temperatura mínima de operación	0 °C
Material del conductor	Cobre estañado	Máxima temperatura	40 °C
Contactos del conector chapado	Níquel	Intervalo de temperatura operativa	0 - 40 °C
Conectar y usar (Plug and Play)	✓	Rango de temperatura de funcionamiento	32 - 104 °F
Medio de transmisión	Par trenzado	Intervalo de temperatura de almacenaje	-10 - 60 °C
Certificación	CE, FCC, RoHS & REACH, CP65		

Detalles técnicos

Certificados de conformidad	CE, Comisión Federal de Comunicaciones (FCC) de Estados Unidos, REACH, RoHS
-----------------------------	---



4002888434034

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.