



## LevelOne FEU-0812 switch No administrado Fast Ethernet (10/100) Negro

Marca : LevelOne

Código del producto: FEU-0812

Nombre del producto : FEU-0812

8 x 10/100Mbps, 1K MAC, 148800pps, 5V/0.6A, 89 x 86 x 23 mm

LevelOne FEU-0812. Tipo de interruptor: No administrado. Puertos tipo básico de conmutación RJ-45 Ethernet: Fast Ethernet (10/100), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 8. Bidireccional completo (Full duplex). Tabla de direcciones MAC: 1000 entradas. Estándares de red: IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3z. Voltaje de entrada DC: 5 V. Conector eléctrico: Toma de entrada de CC



| Características de administración                           |                                                    | Control de energía                                |             |
|-------------------------------------------------------------|----------------------------------------------------|---------------------------------------------------|-------------|
| Tipo de interruptor *                                       | No administrado                                    | Fuente de alimentación incluida *                 | ✓           |
| Puertos e Interfaces                                        |                                                    | Voltaje de entrada DC                             | 5 V         |
| Cantidad de puertos básicos de conmutación RJ-45 Ethernet * | 8                                                  | Corriente de entrada                              | 0.55 A      |
| Puertos tipo básico de conmutación RJ-45 Ethernet *         | Fast Ethernet (10/100)                             | Consumo energético                                | 1,7 W       |
| Conector eléctrico                                          | Toma de entrada de CC                              | Alimentación a través de Ethernet (PoE)           |             |
| Conexión                                                    |                                                    | Energía sobre Ethernet (PoE) *                    | ✗           |
| Estándares de red *                                         | IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3z | Condiciones ambientales                           |             |
| Soporte 10G *                                               | ✗                                                  | Intervalo de temperatura operativa                | 0 - 45 °C   |
| Tecnología de cableado ethernet de cobre                    | 10BASE-T, 100BASE-T                                | Intervalo de temperatura de almacenaje            | -40 - 70 °C |
| Bidireccional completo (Full duplex)                        | ✓                                                  | Intervalo de humedad relativa para funcionamiento | 10 - 90%    |
| Transmisión semidúplex                                      | ✓                                                  | Intervalo de humedad relativa durante almacenaje  | 5 - 90%     |
| Auto MDI / MDI-X                                            | ✓                                                  | Peso y dimensiones                                |             |
| Auto-negociación                                            | ✓                                                  | Ancho                                             | 130,7 mm    |
| Transmisión de datos                                        |                                                    | Profundidad                                       | 52,3 mm     |
| Tabla de direcciones MAC *                                  | 1000 entradas                                      | Altura                                            | 20 mm       |
| Memoria intermedia de paquetes                              | 1,19 MB                                            | Peso                                              | 110 g       |
| Diseño                                                      |                                                    | Empaquetado                                       |             |
| Montaje en rack *                                           | ✗                                                  | Adaptador AC incluido                             | ✓           |
| Apilable *                                                  | ✗                                                  | Tipo de embalaje                                  | Caja        |
| Color del producto                                          | Negro                                              | Ancho del paquete                                 | 145 mm      |
| Indicadores LED                                             | Actividad, Enlace, Poder                           | Profundidad del paquete                           | 80 mm       |
| Desempeño                                                   |                                                    | Altura del paquete                                | 80 mm       |
| Conectar y usar (Plug and Play)                             | ✓                                                  | Peso del paquete                                  | 214 g       |
| Sin ventilador                                              | ✓                                                  | Aprobaciones reguladoras                          |             |
| Control de energía                                          |                                                    | Certificación                                     | CE RoHS     |
| Fuente de energía *                                         | CC                                                 | Datos logísticos                                  |             |
|                                                             |                                                    | País de origen                                    | China       |
|                                                             |                                                    | Código de Sistema de Armomización (SA)            | 85176990    |



4015867226667



4015867206683

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.