

MPN: 6ASFTP-0075BL

## CAT6A S/FTP CU LSZH Ethernet Cable Blue 75cm

The ProXtend CAT6A S/FTP CU ethernet cables are produced with 99.9% pure copper strands and an AWG of 26 to ensure the absolute best performance. The outer jacket of the cable is made from LSZH (Low Smoke Zero Halogen) ensuring low amounts of smoke, toxic fumes, and no acid gasses in case of a fire. The cable is also wrapped in a foil screen that enables protection against electromagnetic interference (EMI), and reinforced with strain relief for increased durability and a snagless latch protection allowing secure installation. Plated with 50"U gold, the connector provides more durability and a higher quality transmission rate. A 50"U gold connector can deliver up to 4x more throughput than a standard metal connector. 50"U is the thickest available and most optimal gold plating.



All ProXtend CAT6 S/FTP CU ethernet cables support PoE+.

Supporting a variety of cable standards, lengths and shieldings, ProXtend is your one stop shop for ethernet cables ensuring that you are always able to find a cable that best suits your network requirements.

## Especificaciones

<b>Certificates</b>	<b>Certificación</b>	REACH
<b>Features</b>	<b>Blindaje de cable</b>	S/FTP (S-STP)
	<b>Cable estándar</b>	Cat6a
	<b>Color producto</b>	Blue
	<b>Conector 1</b>	RJ45
	<b>Conector 1 género</b>	Male
	<b>Conector 2</b>	RJ45
	<b>Conector 2 género</b>	Male
	<b>Estándares de red</b>	IEEE 802.3at
	<b>Longitud del cable</b>	0,75 m
	<b>Material conductor</b>	Copper
	<b>Material cubierta</b>	Low smoke zero halogen (LSZH)
	<b>Plug and play</b>	Yes
	<b>Revestimiento de contactos del conector</b>	Gold
	<b>Tamaño de cable AWG</b>	26
	<b>Tecnología de cableado</b>	10GBase-T
	<b>Tipo de conductor</b>	Stranded
	<b>Velocidad de transferencia de datos</b>	10000 Mbit/s
<b>Operational conditions</b>	<b>Temperatura de almacenamiento</b>	-15 - 60 °C

Operational conditions	(T-T)	-15 - 60 °C
	Temperatura de funcionamiento (T-T)	-10 - 60 °C
Packaging data	Cantidad por pack	1 pieza(s)
	Manual	No
Technical details	Certificados de sostenibilidad	RoHS
	Compliance certificates	RoHS
Vendor information	Brand Name	ProXtend
	Warranty	30 Año/s
Weight & dimensions	Diámetro exterior	6 mm

## Otras imágenes

