Epson EB-X49 - 3LCD projector

portable - 3600 lumens (white) - 3600 lumens (colour) - XGA (1024 x 768) - 4:3 - LAN - white

Group	Projectors
Manufacturer	Epson
Manufacturer item no.	V11H982040
EAN/UPC	8715946680750

Description

Combines the versatility to be positioned just about anywhere with excellent brightness and sharpness, plus low-maintenance performance. Presentations become effortless with the sharp, stylish EB-X49, which offers great performance in a remarkably versatile package. Long lamp life and trusted Epson durability offer peace of mind and minimal maintenance.

Main features

Product Description	Epson EB-X49 - 3LCD projector - portable - LAN - white
Device Type	3LCD projector
Colour	White
Built-in Devices	Speaker
Brightness (White)	3600 lumens
Brightness (Colour)	3600 lumens
Contrast Ratio	16000:1
Resolution	XGA (1024 x 768)
Native Aspect Ratio	4:3
Colour Support	1.07 billion colours
Bulb type	UHE 210 Watt
Bulb life cycle	Up to 6000 hour(s) - normal mode ¦ Up to 12000 hour(s) - economic mode
Video Input	LAN
Speakers	Speaker(s) - integrated
Power	AC 120/230 V (50/60 Hz)
Power Consumption Operational	327 Watt
Dimensions (WxDxH)	30.2 cm x 24.9 cm x 8.7 cm
Weight	2.7 kg

Extended details

	General
Device Type	3LCD projector
Built-in Devices	Speaker
Networking	Ethernet
Enclosure Colour	White
	Projector
Brightness (White)	3600 lumens
Brightness (Colour)	3600 lumens
Contrast Ratio	16000:1
Image Size	76.2 cm - 762 cm
Throw Ratio	1.48 - 1.77:1
Resolution	XGA - XGA (1024 x 768)
Native Aspect Ratio	4:3
Colour Support	1.07 billion colours
Bulb type	UHE 210 Watt
Bulb life cycle	Up to 6000 hour(s) - normal mode ¦ Up to 12000 hour(s) - economic mode
Features	Blackboard Mode, EPSON 3LCD technology, Dynamic Mode, Theater Mode
	Lens
Focus Type	Manual
Lens Aperture	F/1.49-1.72
Zoom Type	Manual
Keystone Correction Direction	Horizontal, vertical
Vertical Keystone Correction	-30 / +30
Horizontal Keystone Correction	-30 / +30
	Video Input
Video Interfaces	VGA, HDMI, composite video
LAN and Wireless Image Transferring Protocols	Wired LAN
	Speakers

Type	Integrated
Sound Output Mode	Mono
Output Power / Channel	5 Watt
Speakers	1 x mixed channel
	Expansion / Connectivity
Interfaces	2 x component video / RGB input - 15 pin HD D-Sub (HD-15) ¦ 1 x VGA output - 15 pin HD D-Sub (HD-15) ¦ 1 x composite video input - RCA ¦ 1 x HDMI - 19 pin HDMI Type A ¦ 1 x audio line-in - RCA x 2 ¦ 1 x audio line-out - mini-phone 3.5 mm ¦ 1 x USB 2.0 - 4 pin USB Type B ¦ 1 x USB 2.0 - 4 pin USB Type A ¦ 1 x serial RS-232C - 9 pin D-Sub (DB-9) ¦ 1 x network - RJ-45 ¦ 2 x audio line-in - mini-phone stereo 3.5 mm
	Miscellaneous
Included Accessories	Wireless remote control
Cables Included	1 x VGA cable
Security Features	Security lock slot (cable lock sold separately), security cable hole
Security Slot Type	Kensington security slot
	Power
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	327 Watt
	Dimensions & Weight
Width	30.2 cm
Depth	24.9 cm
Height	8.7 cm
Weight	2.7 kg
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years ¦ Limited warranty - lamp - 3 years / 1000 hours
	Environmental Parameters
Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Sound Emission	37 dBA
Sound Emission (Economic Mode)	28 dBA

Technical data © 1WorldSync. Subject to technical modifications and errors.