

Ricoh ScanSnap iX2400 Escáner con alimentador automático de documentos (ADF) 600 x 600 DPI A4 Blanco

Marca : Ricoh


Código del producto: PA03870-B101

Nombre del producto : ScanSnap iX2400

Ricoh ScanSnap iX2400. Tamaño máximo de escaneado: 216 x 316 mm, Resolución óptica de escáner: 600 x 600 DPI, Velocidad de escaneo ADF (b/n, A4): 45 ppm. Tipo de escaneado: Escáner con alimentador automático de documentos (ADF), Color del producto: Blanco. Tipo de sensor: Dual CIS. Capacidad del alimentador automático de documentos: 100 hojas. Tamaño máximo de papel ISO A-series: A4, Tipos de media soportados de escaneo: Tarjeta de visita, Post Card(JPN), ISO tamaño de serie A (A0...A9): A4, A5, A6



Exploración		Puertos e Interfaces	
Tamaño máximo de escaneado *	216 x 316 mm	Puerto USB *	✓
Resolución óptica de escáner *	600 x 600 DPI	Versión USB	2.0/3.2 Gen 1 (3.1 Gen 1)
Escaner a color	✓	Conector USB	USB tipo A, USB Tipo C
Escaneado dúplex *	✓	Control de energía	
Velocidad de escaneo ADF (b/n, A4)	45 ppm	Tipo de fuente de alimentación *	Corriente alterna
Diseño		Consumo energético	13 W
Tipo de escaneado *	Escáner con alimentador automático de documentos (ADF)	Frecuencia de entrada AC	50 - 60 Hz
Color del producto *	Blanco	Modo reposo	✓
Pantalla incorporada *	✗	Voltaje de entrada	100 - 240 V
Desempeño		Consumo energético (en suspensión)	1 W
Tipo de sensor *	Dual CIS	Peso y dimensiones	
Capacidad de la entrada		Ancho	292 mm
Capacidad del alimentador automático de documentos	100 hojas	Profundidad	161 mm
Dirección de papel		Altura	159 mm
Tipos de media soportados de escaneo	Tarjeta de visita, Post Card(JPN)	Peso	3,2 kg
Detección de alimentación múltiple	✓	Empaquetado	
Tamaño máximo de papel ISO A-series *	A4	Cantidad por paquete	1 pieza(s)
ISO tamaño de serie A (A0...A9)	A4, A5, A6	Sostenibilidad	
ISO tamaño de serie B (B0...B9)	B4, B5, B6	Certificados de sostenibilidad	ENERGY STAR
Carta	✓	Condiciones ambientales	
Legal	✓	Intervalo de temperatura operativa	5 - 35 °C
Peso del papel	40 - 209 g/m²	Intervalo de humedad relativa para funcionamiento	20 - 80%
		Otras características	
		Certificados de conformidad	RoHS



4939761316524

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.