

CA-SY-521220

Lionfish 15.6" seriesFull flat 15.6" touch screen
POS terminal**15.6 Inches full flat fanless POS system**

The Capture Lionfish is a space saving full flat touch screen POS terminal suitable for a variety of market segments. The Lionfish consists of low power consumption processors and fanless cooling technology to enable the Lionfish to operate with less noise and heat. This makes Lionfish suitable for locations where noise is often taken into consideration.

Ultra-thin appearance with excellent performance

The 15.6" Lionfish POS system has a new design ensure a quiet and smooth operation. It offers flexibility for modular POS peripherals that depend on customers' needs. The novel and elegant appearance with an ultra-thin and smooth design provides greater accessibility and convenience for the customers. The POS system carries an ultra-thin appearance and a new base design that makes the POS system easier to use and is space-saving.



The new base design, which has tilting adjustment angles ranging from 0 to 90 degrees, gives users more flexibility in adjusting for their operation.

Multi-functional, elegant, noise-free and efficient makes Lionfish the ideal choice of Point of Sale system.

Features

- Ready for duty with Intel® Celeron® J6412 Processor
- 15.6-inch TFT LCD, FHD (1920 x 1080px) and HD (1366 x 768px) resolution supported
- True-Flat PCAP (G+G)
- Novel and elegant with ultra-thin and smooth appearance
- M.2 SATA and PCIe*4 maximized the access speed and efficiency
- Fanless technology extends the service life of the machine
- Integrated with the customer display and fold together to save shipment costs and installation time

CA-SY-521220

GENERAL SPECIFICATIONS

Processor	Intel® Celeron® J6412 (1.5M Cache, Max. 2.6 GHz)
System Memory	2 x 260 pin DDR4 SO-DIMM, up to 32GB
Storage	1 x M.2 SATA and PCIe SSD
LCD Panel-I	15.6-inch TFT LCD, 1920 (W) RGB x 1080 (H)
LCD Panel-II	15.6-inch TFT LCD, 1366 (W) RGB x 768 (H)
Touch Panel	True-Flat Projected Capacitive Multi Touch
Speaker	1 x 2W High Quality Speaker

I/O INTERFACE

USB	1 x USB-A 3.2 and 1 x USB-C 3.2 (Bottom) 3 x USB-A 3.0 (Bottom) 2 x USB 2.0 (Panel Side)
LAN	1 x RJ45 10/100/1000Mbps Giga Ethernet
COM	3 x COM (RJ45), w/ RI/5V/12V (Bottom)
HDMI	1 x HDMI Port
Audio	1 x Line-out and 1 x MIC-in
Cash Drawer	1 x RJ11 port supports 2 cash drawer with 12V or 24V by jumper
DC Power Out	1 x +12V Power Out
DC Power In	1 x Standard DIN 4PIN type
Power Adapter	12V@5A, 60W Adapter

MECHANICAL & ENVIRONMENTAL

Dust and Water	IP65 on Front Bezel
Tilt Adjustment	0° ~ 90°
Dimension	389 (W) x 352 (H) x 210 (D)mm
Weight	4.3 kg
Certification	CE/FCC/LVD
Operation System	Windows 10 IoT and Linux
TPM	TPM2.0 (option)
Operation Condition	0°C to +40°C / 20 to 80% without condensation
Storage Condition	-20°C to +55°C / 20 to 85% without condensation

OPTIONAL PERIPHERALS

2nd Display	9.7" (1024X768px) and 10.1" (1280x800px) LCD Display Optional PCAP Touchscreen
Customer Display	VFD and LCD Customer Display
MSR	Bi-directional, Comply with ISO 7811 and Three Track support
Wi-Fi	Wi-Fi IEEE 802.11 a/b/g/n/ac