



FSP Hydro Ti PRO 1000W Unidad de fuente de alimentación ATX ATX3.1 Negro

Marca : FSP

Código del producto: PPA10A3807

Nombre del producto : Hydro Ti PRO 1000W Unidad de fuente de alimentación ATX ATX3.1 Negro

- Compatible con ATX12V V3.0 & EPS12V V2.92
 - Certificación Lambda A++
 - Eficiencia $\geq 94\%$ a carga típica
 - Condensadores japoneses bulk de 450V, 105°C
 - Condensadores electrolíticos japoneses
 - Revestimiento protector de conformación para entornos hostiles
 - Modo ECO: El interruptor de control de ventilador para activar/desactivar la función semi pasiva
 - Ventilador de 135mm con rodamiento dinámico fluido(FDB Fan)
 - Modular completo y un tamaño compacto
- 1000 W, 80 PLUS Titanium, ATX 3.0, 100-240V, 50/60 Hz, 150 x 150 x 85 mm



Control de energía		Puertos e Interfaces	
Potencia total *	1000 W	Conectores de poder PCI Express (6 + 2 pin)	5
Voltaje de entrada AC *	100 - 240 V	Longitud del cable de conectores de alimentación PCI Express (12+4 pines)	700 mm
Frecuencia de entrada AC	50/60 Hz	CPU conector de alimentación (4 +4 pines)	✓
Corriente de entrada	13-6 A	Longitud del cable de alimentación CPU	70 cm
Potencia combinada (3,3 V)	120 W	Tipo de cableado	Totalmente modular
Potencia combinada (+12 V)	1000 W	Desempeño	
Potencia combinada (+5 V)	120 W	Certificación 80 PLUS *	80 PLUS Titanium
Potencia combinada (-12V)	18,6 W	Utilizar con *	PC
Potencia combinada (+5 VSB)	18,6 W	Factor de forma de fuente de alimentación (PSU) *	ATX
Corriente máxima de salida (+3.3V)	20 A	Versión ATX	3.0
Corriente máxima de salida (+12V)	83,33 A	Versión EPS	2.92
Corriente máxima de salida (+5V)	20 A	Nivel de ruido	15 dB
Corriente máxima de salida (-12V)	0,3 A	Tecnología de rodamientos	FDB
Corriente máxima de salida (+5Vsb)	3 A	Diseño	
Eficiencia	94%	Color del producto	Negro
Funciones de protección de poder	Sobrecorriente, Sobreintensidad, Sobrevoltaje, Sobrecalentamiento, Cortocircuito	Tipo de enfriamiento	Activo
		Diámetro de ventilador	13,5 cm
Puertos e Interfaces		Número de ventiladores	1 Ventilador(es)
Alimentador de energía para tarjeta madre *	20+4 pin ATX	Ubicación de ventilador	Superior
Longitud del cable de alimentación de la placa base	60 cm	Interruptor de encendido/apagado integrado	✓
Número de conectores de energía SATA	12	Contenido del embalaje	
Conectores de poder (4 pin) periferales (Molex) *	4	Cables incluidos	CPU, PCIe, Peripheral (Molex), SATA

Peso y dimensiones	
Ancho	150 mm
Profundidad	150 mm
Altura	86 mm



4713224527456

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.