



## Product Feature

- Industrial level DID LCD panel, suitable for extensive 7×24 continuous works.
- Physical resolution of 1920×1080.
- 5ms fast response time, no image ghosting.
- Adapt newest 3D digital filtering and 3D digital noise reduction technology.
- Picture fast response; 178° wide viewing angle; Ensure that the image display is not deformed.
- High fidelity digital processing, brilliant and vivid video.
- Built-in speaker.
- Humanize Menu; Convenient Controller.

## DNle digital image processing

Dynamic optimization



Natural color



Contrast enhancement



Detail enhancement



## DISPLAY CHARACTERISTICS

Mode Name	0070-24122-W-TOUCH
Screen Size	22"
Active Display Area (mm)	476.64mm(W)×268.11mm(H)
Display Mode	16:9
LED Type	TFT-LED
Resolution	1920 × 1080
Display Color	16.7M
Pixel Pitch(mm)	0.630(H)×0.630(V)
Brightness(nits)	350cd/m2 (With Brightness auto adjustment)
Contrast Ratio	1000:1
Viewing Angle	178(H) /178(V)
Response Time	5ms
Backlight	LED

## INPUT&OUTPUT

HDMI 2.0	1
VGA	1
Speaker	YES
Remote controller	YES
USB	1(Touch Screen use)

## Protection

Waterproof	IP 67 at front case and IP 22 at back case
Vandal-proof	Support
3D comb filter	YES
Video Noise Reduction	YES

## POWER&Mount Way

Power	AC100-240V ,50/60Hz
Working Temperature	-30 to +85
Power Consumption	<30W
Menu	English(other languages supported)
Mounting/Weight	Stand mount, VESA mount/8kg
MTBF	50000Hours

## ACCESSORIES

INCLUDED ACCESSORIES	Industrial PSU,Screw, Cable holder, Quick start guide
----------------------	---