



## AISENS Cable USB 3.2 Gen2x2 Aluminio 20Gbps 8K@30Hz 5A 100W, Tipo USB-C/M-USB-C/H, Gris, 0.5 m

**Marca :** AISENS

**Código del producto:** A107-0760

**Nombre del producto :** Cable USB 3.2 Gen2x2 Aluminio 20Gbps 8K@30Hz 5A 100W, Tipo USB-C/M-USB-C/H, Gris, 0.5 m

Cable USB 3.2 Gen2x2 Aluminio 20Gbps 8K@30Hz 5A 100W, Tipo USB-C/M-USB-C/H, Gris, 0.5 m

**AISENS Cable USB 3.2 Gen2x2 Aluminio 20Gbps 8K@30Hz 5A 100W, Tipo USB-C/M-USB-C/H, Gris, 0.5 m:**

Cable USB 3.2 GEN2x2 20Gbps con conector tipo USB-C macho en un extremo y USB-C hembra en el otro.

Ideal para prolongar o cargar su nuevo dispositivo móvil, tablet o portátil USB-C.

El cable ofrece hasta 5 amperios 100W de carga, con lo cual se puede usar para cargar su dispositivo móvil, tablet, portátil de hasta 100W etc.

Velocidad de transferencia de datos de hasta 20Gbps.

AISENS Cable USB 3.2 Gen2x2 Aluminio 20Gbps 8K@30Hz 5A 100W, Tipo USB-C/M-USB-C/H, Gris, 0.5 m.

Longitud de cable: 0,5 m. Conector 1: USB C, Conector 2: USB C, Versión USB: USB 3.2 Gen 2x2, Tasa de transferencia (máx): 20 Gbit/s, Color del producto: Gris



| Características                                      |                     | Peso y dimensiones              |                       |
|------------------------------------------------------|---------------------|---------------------------------|-----------------------|
| Versión USB *                                        | USB 3.2 Gen 2x2     | Longitud de cable *             | 0,5 m                 |
| Conector 1 *                                         | USB C               | <b>Empaquetado</b>              |                       |
| Conector 2 *                                         | USB C               | Tipo de embalaje                | Envase para colgar    |
| Género del conector 1 *                              | Macho               | Ancho del paquete               | 160 mm                |
| Género del conector 2 *                              | Hembra              | Profundidad del paquete         | 120 mm                |
| Factor de forma de conector 1                        | Derecho             | Altura del paquete              | 10 mm                 |
| Factor de forma de conector 2                        | Derecho             | Peso del paquete                | 32 g                  |
| Rango máximo de transferencia de datos               | 20000 Mbit/s        | <b>Contenido del embalaje</b>   |                       |
| Tasa de transferencia (máx)                          | 20 Gbit/s           | Cantidad por paquete *          | 1 pieza(s)            |
| Tipo de cable                                        | Cable redondo       | <b>Sostenibilidad</b>           |                       |
| Entrega de energía USB (USB Power Delivery) de hasta | 100 W               | Cumplimiento de sostenibilidad  | ✓                     |
| Color del producto *                                 | Gris                | <b>Aprobaciones reguladoras</b> |                       |
| Máxima resolución                                    | 7680 x 4320 Pixeles | Certificados de conformidad     | RoHS                  |
| Máxima velocidad de actualización                    | 60 Hz               | <b>Datos logísticos</b>         |                       |
| <b>Control de energía</b>                            |                     | Cantidad por caja               | 250 pieza(s)          |
| Corriente de entrada (máx.)                          | 5 A                 | Ancho de la caja principal      | 300 mm                |
|                                                      |                     | Longitud de la caja             | 460 mm                |
|                                                      |                     | Alto de la caja principal       | 280 mm                |
|                                                      |                     | Peso del envase completo        | 8 kg                  |
|                                                      |                     | Volumen de caja                 | 38640 cm <sup>3</sup> |
|                                                      |                     | Volumen del paquete             | 192 cm <sup>3</sup>   |



8436574709650

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.