



StarTech.com Tarjeta PCI Express de 4 Puertos USB 3.0 (5Gbps) - 2 Externos y 2 Internos - con Alimentación SATA - con Soporte para UASP - con 2 Conectores Internos IDC Tipo Placa Base

Marca : StarTech.com

Código del producto: PEXUSB3S2EI

Nombre del producto : Tarjeta PCI Express de 4 Puertos USB 3.0 (5Gbps) - 2 Externos y 2 Internos - con Alimentación SATA - con Soporte para UASP - con 2 Conectores Internos IDC Tipo Placa Base

- Flexibilidad para conectar dispositivos USB 3.2 Gen 1 externos e internos y compatibilidad con UASP
 - Configuración rápida y sin problemas con Windows 8 nativo, así como acoplamiento a sistemas de perfil estándar o perfil bajo
 - Su retrocompatibilidad le posibilita ahorrar dinero al poder conectarlo con dispositivos USB 2.0 y 1.x ya existentes
 - Transfiere archivos de gran tamaño a una velocidad impresionante, con soporte para una capacidad de transmisión de hasta 5Gbps
 - Conector opcional SATA de alimentación que ofrece hasta 900mA por puerto para dispositivos USB que requieren mucha potencia
 - Interfaz PCIe x1, conforme con las especificaciones para PCI Express 2.0
 - Configurado con soporte de perfil completo, incluye soporte de media altura
- StarTech Tarjeta PCI Express de 4 Puertos USB 3.0 (5Gbps) - 2 Externos y 2 Internos - con Alimentación SATA - con Soporte para UASP - con 2 Conectores Internos IDC Tipo Placa Base (PEXUSB3S2EI)



Puertos e Interfaces		Requisitos del sistema	
Interfaz de host *	PCIe		Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 11, Windows 11 x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Interfaz de salida *	SATA, USB 3.2 Gen 1 (3.1 Gen 1)		
Factor de forma de la tarjeta de expansión	Full-height / Low-profile		
Estándar de la tarjeta de expansión	PCI 2.0		
Cantidad de puertos tipo A USB 3.2 Gen 1 (3.1 Gen 1)	2		
Cantidad de puertos SATA internos	1		
Diseño		Sistema operativo Windows soportado	
Interno *	✓		
Color del producto	Metálico, Rojo		
Longitud máxima del cable	3 m		
Tiempo medio entre fallos	1920042 h		
Características		Sistema operativo Windows soportado	
Circuito integrado	Renesas / NEC - μPD720201		
Tasa de transferencia de datos (max)	5 Gbit/s		
apoyo UASP	✓	Sistema operativo Windows soportado	
Condiciones ambientales			
Intervalo de temperatura operativa	5 - 50 °C		
Intervalo de temperatura de almacenaje	-25 - 70 °C		
Intervalo de humedad relativa para funcionamiento	20 - 80%		

Requisitos del sistema	
Sistema operativo de servidor soportado	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Detalles técnicos	
Certificados de conformidad	CE, RoHS
Peso y dimensiones	
Ancho	18 mm
Profundidad	92 mm
Altura	120 mm
Peso	53 g
Empaquetado	
Soportes de montaje incluidos	✓
Controladores incluidos	✓
Manual de usuario	✓
Ancho del paquete	143 mm
Profundidad del paquete	175 mm
Altura del paquete	33 mm
Peso del paquete	143 g
Datos logísticos	
Código de Sistema de Armomización (SA)	84733020
Cantidad por caja	60 pieza(s)
Ancho de la caja principal	382 mm
Longitud de la caja	500 mm
Alto de la caja principal	318 mm
Otras características	
Distancia de funcionamiento máximo	3 m



0065030860338



065030860338



0723856593525



723856593525

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.