



FSP HYPER 80+ PRO 550W Unidad de fuente de alimentación ATX ATX3.1 Negro

Marca : FSP

Código del producto: 9PA5509407

Nombre del producto : HYPER 80+ PRO 550W Unidad de fuente de alimentación ATX ATX3.1 Negro

FSP HYPER 80+ PRO 550W Unidad de fuente de alimentación ATX ATX3.1 Negro. Potencia total: 550 W, Voltaje de entrada AC: 200 - 240 V, Corriente de entrada: 4.5 A. Alimentador de energía para tarjeta madre: 24-pin ATX, Tipo de cableado: No modular. Utilizar con: PC, Factor de forma de fuente de alimentación (PSU): ATX, Certificación 80 PLUS: 80 PLUS Bronze. Color del producto: Negro, Tipo de enfriamiento: Activo, Diámetro de ventilador: 12 cm. Certificación: IEC 62368



Control de energía		Puertos e Interfaces	
Potencia total *	550 W	Conector de alimentación EPS (4+4 pines)	✓
Voltaje de entrada AC *	200 - 240 V	Conectores de poder PCI Express (6 + 2 pin)	2
Corriente de entrada	4.5 A	Conector de poder floppy	1
Factor de poder	0,9	Conector a unidad de disquetes	✓
Corrección del factor de potencia tipo (PFC)	Activo	Tipo de cableado	No modular
Potencia combinada (3,3 V)	85 W	Desempeño	
Potencia combinada (+12 V)	549,6 W	Certificación 80 PLUS *	80 PLUS Bronze
Potencia combinada (+5 V)	85 W	Utilizar con *	PC
Potencia combinada (-12V)	3,6 W	Factor de forma de fuente de alimentación (PSU) *	ATX
Potencia combinada (+5 VSB)	12,5 W	Versión ATX	2.4
Corriente máxima de salida (+3.3V)	16 A	Versión EPS	2.92
Corriente máxima de salida (+12V)	45,8 A	Diseño	
Corriente máxima de salida (+5V)	16 A	Color del producto	Negro
Corriente máxima de salida (-12V)	0,3 A	Tipo de enfriamiento	Activo
Corriente máxima de salida (+5Vsb)	2,5 A	Diámetro de ventilador	12 cm
Tiempo de espera	17 ms	Número de ventiladores	1 Ventilador(es)
Eficiencia	85%	Iluminación	✗
Funciones de protección de poder	Sobreintensidad, Sobretensión, Sobrevoltaje, Cortocircuito	Aprobaciones reguladoras	
Puertos e Interfaces		Certificación	IEC 62368
Alimentador de energía para tarjeta madre *	24-pin ATX	Peso y dimensiones	
Número de conectores de energía SATA	5	Ancho	150 mm
Conectores de poder (4 pin) periferales (Molex) *	2	Profundidad	140 mm
		Altura	86 mm
		Peso	1,25 kg
		Detalles técnicos	
		Cumplimiento de sostenibilidad	✓

Detalles técnicos

Certificados de sostenibilidad

ErP



4711498480569

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.