

CyberPower PDU81405 unidad de distribución de energía (PDU) 24 salidas AC 0U Negro

Marca : CyberPower

Código del producto: PDU81405

Nombre del producto : PDU81405

- Protección contra sobrecargas
 - Ultra Ultra Low Power Consumption
 - Carcasa metálica de calidad en el sector
 - Pantalla LCD a color configurable por el usuario
 - Pantalla LCD giratoria para una orientación adecuada de la pantalla
 - Actualización de firmware a través de USB
 - Firmware actualizable por el usuario
 - Soportes de montaje ajustables
 - Bloqueo de receptáculo IEC
 - Tomas de corriente controlables con secuenciación de la alimentación
 - Trabajo bajo temperatura alta
 - ± 1% de precisión de medición
 - Visor de carga en tiempo real digital
 - Diseño LCD intercambiable en caliente
 - Indicador de estado LED
 - Software de gestión PowerPanel
 - Bandeja de retención de cables
- Unidades de distribución de potencia

Diseño		Control de energía	
PDU tipos *	Regulado, Monitorizado, Conmutado	Voltaje nominal de entrada *	200-240 V
Tipo	Monofásico	Frecuencia de entrada AC	50 / 60 Hz
Capacidad del rack *	0U	Máxima corriente *	16 A
Montaje	Vertical	Aprobaciones reguladoras	
Material de la carcasa	Metal	Certificación	CE, EN 55032 Class A
Color del producto	Negro	Condiciones ambientales	
Pantalla	LCD	Intervalo de temperatura operativa	0 - 55 °C
Puertos e Interfaces		Intervalo de temperatura de almacenaje	-15 - 60 °C
Cantidad de salidas AC *	24 salidas AC	Intervalo de humedad relativa para funcionamiento	0 - 95%
Conector	IEC 60309	Intervalo de humedad relativa durante almacenaje	0 - 95%
Tipo de salida AC *	C13 acoplador, C19 acoplador	Altitud de funcionamiento	0 - 3500 m
Puerto serial	1	Altitud no operativa	0 - 15000 m
Ethernet LAN (RJ-45) cantidad de puertos	3	Peso y dimensiones	
Características		Ancho	1665 mm
Conexión en cadena	✓	Profundidad	56 mm
Indicadores LED	✓	Altura	48 mm
Longitud de cable	3,05 m	Peso	7 kg
Características de administración		Empaquetado	
Protocolos de red compatibles	IPv4/v6, SNMPv1/v3, HTTP/HTTPS, TCP/IP, UDP, DHCP, NTP, DNS, SMTP, SSH, SSL, TLS, Telnet, FTP, and Syslog	Peso del paquete	8,9 kg
Firmware actualizable	✓	Ancho del paquete	1895 mm
Firmware actualizable mediante	USB	Profundidad del paquete	185 mm
		Altura del paquete	115 mm



4712856277210

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.