

StarTech.com Tarjeta Adaptador de Red Ethernet Gigabit Combo con Hub Concentrador USB 3.0 (5Gbps) de 3 Puertos


Marca : StarTech.com

Código del producto: PEXUSB3S3GE

Nombre del producto : Tarjeta Adaptador de Red Ethernet Gigabit Combo con Hub Concentrador USB 3.0 (5Gbps) de 3 Puertos



- Deje disponible una ranura PCIe mediante la consolidación de 3x puertos USB 3.2 Gen 1 & 1x puerto Ethernet Gigabit en una sola tarjeta
 - Diseño de perfil doble, el cual ofrece flexibilidad de instalación para ordenadores de perfil bajo y perfil estándar
 - Su retrocompatibilidad le posibilita ahorrar dinero, al poder conectarla con sus dispositivos USB 2.0 y 1.x ya existentes
 - Ideal para dispositivos USB que requieren mucha potencia, con alimentación SATA opcional de hasta 900mA por puerto
 - Interfaz PCIe x1, conforme con las especificaciones para PCI Express 2.0
 - Compatibilidad con WOL ("Wake-On-LAN", reinicio mediante red), Ethernet de consumo eficiente de energía (EEE), tramas Jumbo, control de flujo de dúplex completo, etiquetado VLAN y codificación de prioridad de capa 2
- StarTech Tarjeta Adaptador de Red Ethernet Gigabit Combo con Hub Concentrador USB 3.0 (5Gbps) de 3 Puertos - Ladrón USB Interno (PEXUSB3S3GE)



Puertos e Interfaces

Tecnología de conectividad *	Alámbrico
Interfaz de host *	PCI Express
Interfaz *	Ethernet
Ethernet LAN (RJ-45) cantidad de puertos	1
Número de puertos USB 3.2 Gen 1 (3.1 Gen 1)	3
Versión USB	3.2 Gen 1 (3.1 Gen 1)
Versión PCI	2.0
Forma de factura de tarjeta PCI	Altura completa (bajo perfil)

Conexión

Rango máximo de transferencia de datos *	5000 Mbit/s
Estándares de red *	IEEE 802.1p, IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
Ethernet	✓
Ethernet LAN, velocidad de transferencia de datos	10,100,1000 Mbit/s
Tecnología de cableado	10/100/1000BaseT(X)
Conexión de redes	✓
IEEE Auto MDIX	✓
Bidireccional completo (Full duplex)	✓
Jumbo Frames, soporte	✓
Auto-negociación	✓
Tramas Jumbo	9000
Etiquetado VLAN	✓

Diseño

Color del producto	Metálico, Rojo
--------------------	----------------

Requisitos del sistema

Sistema operativo de servidor soportado	Windows Server 2008 R2, Windows Server 2012
---	---

Condiciones ambientales

Intervalo de temperatura operativa	5 - 50 °C
Intervalo de temperatura de almacenaje	-25 - 70 °C
Intervalo de humedad relativa para funcionamiento	20 - 80%

Peso y dimensiones

Ancho	18 mm
Profundidad	77 mm
Altura	120 mm
Peso	60 g

Empaquetado

Controladores incluidos	✓
Cantidad por paquete	1 pieza(s)
Ancho del paquete	143 mm
Profundidad del paquete	174 mm
Altura del paquete	33 mm
Peso del paquete	150 g

Contenido del embalaje

Soportes de montaje incluidos	✓
Manual de usuario	✓

Detalles técnicos

Certificados de conformidad	RoHS
-----------------------------	------

Diseño		Datos logísticos	
Interno *	✓	Código de Sistema de Armomización (SA)	85176990
Circuito integrado	Renesas / NEC - μPD720201, Realtek - RTL8153	Ancho de la caja principal	378 mm
Indicadores LED	Actividad, Enlace	Longitud de la caja	496 mm
Tiempo medio entre fallos	1920042 h	Alto de la caja principal	320 mm
Certificación	CE, FCC	Cantidad por caja	60 pieza(s)
Requisitos del sistema		Otras características	
Sistema operativo Windows soportado	Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64	Soporte de control de flujo	✓
		Tasa de transferencia de datos USB apoyo UASP	5000 Mbit/s ✓
Sistema operativo Linux soportado	✓		



0065030860796



065030860796

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.