



Epson EB-2250U - 3LCD projector

5000 lumens (white) - 5000 lumens (colour) - WUXGA (1920 x 1200) - 16:10 - 1080p - LAN - white

Group	Projectors
Manufacturer	Epson
Manufacturer item no.	V11H871040
EAN/UPC	8715946628646

Description

Epson EB-2250U - 3LCD projector - 5000 lumens (white) - 5000 lumens (colour) - WUXGA (1920 x 1200) - 16:10 - 1080p - LAN - white

Main features

Product Description	Epson EB-2250U - 3LCD projector - LAN - white
Device Type	3LCD projector - 1080p
Colour	White
Brightness (White)	5000 lumens
Brightness (Colour)	5000 lumens
Contrast Ratio	400:1 / 15000:1 (dynamic)
Resolution	WUXGA (1920 x 1200)
Native Aspect Ratio	16:10
Colour Support	1.07 billion colours
Bulb type	300 Watt
Bulb life cycle	Up to 5000 hour(s) - normal mode Up to 10000 hour(s) - economic mode
Video Input	LAN
Speakers	Speaker(s) - integrated
Power	AC 230V (50 - 60 Hz)
Power Consumption Operational	420 Watt
Dimensions (WxDxH)	37.7 cm x 29.1 cm x 11 cm
Weight	4.8 kg

Extended details

General

Device Type	3LCD projector - 1080p
Networking	Ethernet



Enclosure Colour	White
Projector	
Brightness (White)	5000 lumens
Brightness (Colour)	5000 lumens
Brightness (Reduced)	3800 lumens
Contrast Ratio	400:1 / 15000:1 (dynamic)
Image Size	127 cm - 762 cm
Projection Distance	1.5 m - 9 m
Throw Ratio	1.38 - 2.28:1
Digital Zoom Factor	1.6x
Resolution	WUXGA - WUXGA (1920 x 1200)
Native Aspect Ratio	16:10
Colour Support	1.07 billion colours
Bulb type	300 Watt
Bulb life cycle	Up to 5000 hour(s) - normal mode Up to 10000 hour(s) - economic mode
Features	sRGB colour profile, Blackboard Mode, Auto Vertical Keystone, Split Screen, DICOM Simulation Mode, Direct Power On, Direct Power Off, Dynamic Mode, instant on/off
Lens	
Focus Type	Manual
Lens Aperture	F/1.5-2.0
Keystone Correction Direction	Horizontal, vertical
Vertical Keystone Correction	-30 / +30
Horizontal Keystone Correction	-30 / +30
Video Input	
LAN and Wireless Image Transferring Protocols	Wired LAN
Speakers	
Type	Integrated
Sound Output Mode	Mono
Output Power / Channel	16 Watt
Speakers	1 x mixed channel
Expansion / Connectivity	
Interfaces	1 x USB 2.0 - 4 pin USB Type A 1 x USB 2.0 - 4 pin USB Type B (management) 1 x network - RJ-45 1 x VGA output - 15 pin HD D-Sub (HD-15) 1 x composite video input - RCA 2 x component video / RGB input - 15 pin HD D-Sub (HD-15) 2 x audio line-in - mini-phone stereo 3.5 mm 1 x audio line-out - mini-phone stereo 3.5 mm 1 x HDMI - 19 pin HDMI Type A 1 x Mobile High-Definition Link (MHL) / HDMI - 19 pin HDMI Type A
Miscellaneous	
Included Accessories	Wireless remote control
Cables Included	1 x VGA cable
Security Features	Security lock slot (cable lock sold separately), password protection
Power	
Power Source	AC



Nominal Voltage	AC 230V (50 - 60 Hz)
Power Consumption Operational	420 Watt
Power Consumption Stand by	0.5 Watt
Software / System Requirements	
Software Included	EasyMP Network Projection, EasyMP Slide Converter, EasyMP Monitor, EasyMP Multi PC Projection
Dimensions & Weight	
Width	37.7 cm
Depth	29.1 cm
Height	11 cm
Weight	4.8 kg
Manufacturer Warranty	
Service & Support	Limited warranty - 5 years - carry-in
Environmental Parameters	
Min Operating Temperature	5 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80%
Sound Emission	39 dBA
Sound Emission (Economic Mode)	29 dBA

Technical data © CNET Content Solutions. Subject to technical modifications and errors.