Industry Hub 7 x USB 5 Gbps Type-A with 8 kV ESD protection and DIN rail mounting

Description

This solid industry capable USB Hub by Delock can be connected to a computer via the USB Type-A interface. It expands the computer by **seven USB Type-A connectors**.

Screw connection and mounting option

Each USB port has two **screw holes with M3 thread**. Appropriate cables can be plugged in and screwed into the screw holes. This ensures a secure data connection even in mobile environments.
In addition, the hub comes with **wall mounting plates** and a **DIN rail bracket**, making it perfect for installation in an industrial environment.

ESD fuse

The USB ports are protected against electrostatic discharges up to **8 kV**.

Power Supply

If necessary, an optional power supply or an optional power cable can be connected to the power socket. A **voltage between 7 - 24 V** can be applied to the terminal power connection, and to the DC connection.



Item no. 60791

EAN: 4043619607914

Country of origin: China

Package: Box

Technical details

- Connectors:
  1 x USB 5 Gbps Type-B female
  7 x USB 5 Gbps Type-A female
  1 x 7 - 24 V DC jack
  1 x 7 - 24 V 2 pin terminal power connector
- Chipset: VIA VL817
- Data transfer rate up to 5 Gbps
- Bootable
- Plug & Play
- 8 x LED indicator
- Robust metal housing
- USB ports with screw holes
- Pitch of screw hole USB Type-A: ca. 19 mm
- Pitch of screw hole USB Type-B: ca. 16.5 mm

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

- Thread size: M3
- Removable wall-mount brackets
- Power supply: Bus-powered or Self-powered
- Flexible power supply with 7 V to 24 V
- ESD protection up to 8 kV for all ports
- Operating temperature: -40 °C ~ 85 °C
- Storage temperature: -40 °C ~ 125 °C
- Colour: black
- Dimensions (LxWxH): ca. 141 x 67 x 28 mm

Specification of power connector

- DC: 7 - 24 V
- Dimensions:
  inside: ø ca. 2.5 mm
  outside: ø ca. 5.5 mm
  length: ca. 10 mm
- terminal: 7 - 24 V

System requirements

- Linux Kernel 6.2 or above
- Mac OS 13.1 or above
- Windows 10/10-64/11
- Windows Server 2022
- PC or laptop with a free USB Type-A port

Package content

- Hub USB
- 1 x cable USB A male to USB B male, length ca. 1 m
- 2 x wall mounting brackets
- 1 x mounting for 35 mm DIN rail
- 1 x 2 pin terminal block
- Screws
- Dowel
- User manual

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Images







All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Allgemein

Funktion:	Plug & Play Bootfähig
Unterstütztes Betriebssystem:	Windows 10 32-Bit Windows 10 64-Bit Windows 11 Windows Server 2022 Mac OS 13.1 oder höher Linux Kernel 6.2 oder höher
LED Anzeige:	8 x

Schnittstelle

Anschluss 1:	1 x USB 5 Gbps Typ-B Buchse
Anschluss 2:	7 x USB 5 Gbps Typ-A Buchse
Anschluss 3:	1 x 7 - 24 V DC Strombuchse
Anschluss 4:	1 x 7 - 24 V 2 Pin Terminal Stromanschluss

Technische Eigenschaften

Chipsatz:	VIA VL817
Datentransferrate:	5 Gbps
Lagerungstemperatur:	-40 °C ~ 125 °C
Betriebstemperatur:	-40 °C ~ 85 °C

Physikalische Eigenschaften

Länge:	141 mm
Breite:	67 mm
Höhe:	28 mm
Farbe:	schwarz

Manufacturer information

Street	Beeskowdamm 13/15

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**