

HP LaserJet M209dw - Printer - B/W

Duplex - laser - A4/Legal - 600 x 600 dpi - up to 29 ppm - capacity: 150 sheets - USB 2.0 - LAN - Wi-Fi(n) - Bluetooth LE

Group	Printers
Manufacturer	HP
Manufacturer item no.	6GW62F#B19
EAN/UPC	0194850664267



Description

A high-productivity compact mono laser printer with the fastest two-sided printing in its class and the time-saving HP Smart app. Count on more reliable connections and a worry-free experience and get legendary HP quality.

Main features

Product Description	HP LaserJet M209dw - printer - B/W - laser
Printer Type	Workgroup printer - laser - B/W
Number of Users	1-5 users
Weight	5.6 kg
Localisation	English, German, French, Italian, Spanish / Europe
Media Size Class	A4/Legal
Max Media Size	Legal (216 x 356 mm), A4 (210 x 297 mm)
Min Media Size (Custom)	102 mm x 152 mm
Max Media Size (Custom)	216 mm x 356 mm
Print Speed	Up to 29 ppm - B/W (ISO/IEC 24734) - A4 (210 x 297 mm) Up to 29 ppm - black landscape - A5 (148 x 210 mm) Up to 30 ppm - B/W (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm) Up to 7 ppm - black portrait - A5 (148 x 210 mm) Up to 19 inch/min - B/W duplex - ANSI A (Letter) (216 x 279 mm)
Max Resolution (B&W)	600 x 600 dpi
Automatic Duplexing	Yes
Interface	USB 2.0, LAN, Wi-Fi(n), Bluetooth LE
AirPrint Enabled	Yes
Processor	500 MHz
RAM Installed (Max)	64 MB (64 MB)
Language Simulation	URF, PWG, PCLmS
Media Type	Envelopes, labels, plain paper, card stock, postcards
Total Media Capacity	150 sheets
Monthly Duty Cycle (max)	20000 pages
Recommended Monthly Volume	200 - 2000 pages
Networking	Print server

Power	AC 230V
System Requirements	Linux, Microsoft Windows Server 2008 R2 x64 Edition, Microsoft Windows 7 (32/64 bits), Windows 8 (32/64 bits), Microsoft Windows Server 2012 x64 Edition, Windows 8.1 (32/64 bits), Microsoft Windows Server 2012 R2 x64 Edition, Microsoft Windows Server 2008 R2 SP1 (64-bits), Windows 10 (32/64 bits), Microsoft Windows Server 2016 (64-bit), Apple macOS 10.13, Apple macOS 10.14, Apple macOS 10.15
Environmental Standards	EPEAT Silver
Dimensions (WxDxH)	35.5 cm x 27.95 cm x 20.5 cm

Extended details

	General
Printer Type	Workgroup printer - laser - monochrome
Number of Users	1-5 users
Localisation	English, German, French, Italian, Spanish / Europe
	Printer
Print Speed	Up to 29 ppm - B/W (ISO/IEC 24734) - A4 (210 x 297 mm) ¦ Up to 29 ppm - black landscape - A5 (148 x 210 mm) ¦ Up to 30 ppm - B/W (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm) ¦ Up to 7 ppm - black portrait - A5 (148 x 210 mm) ¦ Up to 19 inch/min - B/W duplex - ANSI A (Letter) (216 x 279 mm)
Connectivity Technology	Wireless
Interface	USB 2.0, LAN, Wi-Fi(n), Bluetooth LE
AirPrint Enabled	Yes
Max Resolution (B&W)	600 x 600 dpi
Automatic Duplexing	Yes
Language Simulation	URF, PWG, PCLmS
	Processor
Processor	500 MHz
	RAM
RAM Installed (Max)	64 MB / 64 MB (max)
	Media Handling
Media Type	Envelopes, labels, plain paper, card stock, postcards
Media Size Class	A4/Legal
Max Media Size	Legal (216 x 356 mm), A4 (210 x 297 mm)
Min Media Size (Custom)	102 mm x 152 mm
Max Media Size (Custom)	216 mm x 356 mm
Media Sizes	ANSI A (Letter) (216 x 279 mm), Legal (216 x 356 mm), Executive (184 x 267 mm), A4 (210 x 297 mm), A5 (148 x 210 mm), A6 (105 x 148 mm), 102 x 152 mm, JIS B5 (182 x 257 mm), 216 x 356 mm
Media Weight	60 g/m ² - 163 g/m ²
Media Weight (lbs)	16 lbs - 43 lbs
Total Media Capacity	150 sheets

Media Feeders	Input tray: 1 x automatic - 150 sheets - Legal (216 x 356 mm) weight: 60 g/m ² - 163 g/m ² - (16 lbs (min) - 43 lbs (max)) Output tray: 1 - 100 sheets - Legal (216 x 356 mm)
Output Trays Capacity	100 sheets
	Duty Cycle
Monthly Duty Cycle (max)	20000 pages
Recommended Monthly Volume	200 - 2000 pages
	Networking
Networking	Print server
Remote Management Protocol	SNMP 1, SNMP 2, SNMP 3, HTTP, HTTPS, SLP, DHCP
Security Protocols & Features	SSL, Apple Bonjour, TLS
	Expansion / Connectivity
Connections	1 x USB 2.0 - 4 pin USB Type B 1 x LAN - RJ-45
	Miscellaneous
Included Accessories	Setup poster
Consumables Included	1 x toner cartridge (black) - up to 700 pages
Features	Paper sensor
Compliant Standards	UL, TUV GS, BSMI, CCC, FCC, IEC 60825-1, FCC CFR47 Part 15 C, EN 60825-1, KC, EAC, EN 62479:2010, RCM, BIS, EN 61000-3-3:2013, EN 62311:2008, EN 61000-3-2:2014, IEC 62479:2010, IEC 62311:2007, FCC CFR47 Part 15 B Class B, EN 55032:2012, RSS-102 Issue 5, SIRIM, RSS-247 Issue 1, FCC CFR47 Part 15 E, ICES-003 issue 6, EN 62368-1:2014, CAN/CSA-C22.2 No. 62368-1, CISPR 32:2012, EN 300 328 V2.1.1, UL 62368-1, IEC 60950-1:2005 (ed.2)+A1:2009+A2:2013, CISPR 32:2015, EN 55032:2015+AC:2016 Class B, RED 2014/53/EU, EN 55035:2017, Mercury-free, EN 301 893 V2.1.1, DE-UZ 205, EN 301 489-17 V3.2.0, IEC 62368-1: 2014, EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013, EN 300 440-1 V2.1.1, EN 301 489-1 V2.2.3
	Power
Power Device	Power supply - internal
Voltage Required	AC 230V
Frequency Required	50/60 Hz
Power Consumption Operational	420 Watt
Power Consumption Stand by	2 Watt
Power Consumption Sleep	0.5 Watt
	Software / System Requirements
OS Required	Linux, Microsoft Windows Server 2008 R2 x64 Edition, Microsoft Windows 7 (32/64 bits), Windows 8 (32/64 bits), Microsoft Windows Server 2012 x64 Edition, Windows 8.1 (32/64 bits), Microsoft Windows Server 2012 R2 x64 Edition, Microsoft Windows Server 2008 R2 SP1 (64-bits), Windows 10 (32/64 bits), Microsoft Windows Server 2016 (64-bit), Apple macOS 10.13, Apple macOS 10.14, Apple macOS 10.15
	Environmental Standards
EPEAT Compliant	EPEAT Silver
Blue Angel	Yes
ENERGY STAR	Yes

	Manufacturer Warranty
Service & Support	Limited warranty - 1 year
	Environmental Parameters
Min Operating Temperature	15 °C
Max Operating Temperature	32.5 °C
Humidity Range Operating	10 - 80%
Sound Emission (Idle)	15 dBA
Sound Emission (Operating)	54 dBA
	Dimensions & Weight
Width	35.5 cm
Depth	27.95 cm
Height	20.5 cm
Weight	5.6 kg
	Dimensions & Weight (Shipping)
Width (Shipping)	43.2 cm
Depth (Shipping)	33.1 cm
Height (Shipping)	27.2 cm
Weight (Shipping)	7.3 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.