

D-Link DGS 1510-28X - Switch - L3

smart - 24 x 10/100/1000 + 4 x 10 Gigabit SFP+ - desktop - rack-mountable

Group	Network Equipment
Manufacturer	D-Link
Manufacturer item no.	DGS-1510-28X/E
EAN/UPC	0790069467974



Description

D-Link DGS 1510-28X - Switch - L3 - smart - 24 x 10/100/1000 + 4 x 10 Gigabit SFP+ - desktop, rack-mountable

Main features

Product Description	D-Link DGS 1510-28X - switch - 28 ports - smart - rack-mountable
Device Type	Switch - 28 ports - L3 - smart - stackable
Enclosure Type	Rack-mountable
Subtype	Gigabit Ethernet
Ports	24 x 10/100/1000 + 4 x 10 Gigabit SFP+
Performance	Switching capacity: 128 Gbps Forwarding rate (64-byte packets): 95.24 Mpps Stacking bandwidth: 40 Gbps
Capacity	Static MAC entries: 512 Packet buffer size: 1.5 MB IGMP groups: 512 Layer 2 multicast addresses: 128 VLAN IDs: 4094 MLD groups: 512 ACL rules: 768
MAC Address Table Size	16384 entries
Jumbo Frame Support	9216 bytes
Routing Protocol	IGMP, IGMPv2, IGMPv3, MSTP, RSTP, STP, MLD, MLDv2, static IPv4 routing, static IPv6 routing
Remote Management Protocol	CLI, ICMP, SNMP 3, SNMP 2c, SNMP 1, RMON 1, SSH-2, TFTP, Telnet, DHCP
Features	Flow control, auto-negotiation, full duplex mode, auto-uplink (auto MDI/MDI-X), store and forward, Smart Fan, D-Link SIM, HOL Blocking Prevention, IGMP snooping, MLD snooping, loopback detection, port mirroring, Multicast filtering function, ERPS, Asymmetric VLAN, auto voice VLAN, MAC based VLAN, tagged VLAN, Protocol-based VLANs support, GVRP, CoS, DRR, SPQ, WRR, bandwidth control, ACL support, Port Security, Broadcast Storm Control, Multicast Storm Control, Unicast Storm Control, DAI, BPDU protection, DoS attack prevention, IPMB, Guest VLAN, Cable Diagnostics Function, sFlow, DHCP client, DHCP server, Green Technology, dual image support

Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1ab (LLDP), IEEE 802.1D, IEEE 802.1s, IEEE 802.1w, IEEE 802.1p, IEEE 802.1Q
Power	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH)	44 cm x 21 cm x 4.4 cm
Weight	2 kg
Localisation	Europe

Technical data © 1WorldSync. Subject to technical modifications and errors.