



TP-Link DeltaStream DS-P7001-04 terminal de líneas ópticas

**Marca :** TP-Link

**Familia de productos:** DeltaStream

**Código del producto:** DS-P7001-04

**Nombre del producto :** DS-P7001-04



TP-Link DeltaStream DS-P7001-04. Relación de separación de GPON (máx.): 1:128, Distancia lógica máxima (GPON): 20000 m. Puertos ascendentes: Gigabit Ethernet. Voltaje de entrada AC: 100 - 240 V, Frecuencia de entrada AC: 50 - 60 Hz, Rango de voltaje DC: 38.4 - 72 V. Ancho: 440 mm, Profundidad: 180 mm, Altura: 44 mm



| Características                                 |                  | Puertos e Interfaces                              |             |
|-------------------------------------------------|------------------|---------------------------------------------------|-------------|
| Ruta estática                                   | ✓                | Cantidad de puertos SFP/SFP+                      | 1           |
| DHCP, servidor                                  | ✓                | Control de energía                                |             |
| Relé DHCP                                       | ✓                | Voltaje de entrada AC                             | 100 - 240 V |
| IGMP                                            | ✓                | Frecuencia de entrada AC                          | 50 - 60 Hz  |
| Intrusión de rendimiento de multidifusión (MLD) | ✓                | Rango de voltaje DC                               | 38.4 - 72 V |
| Calidad de servicio (QoS) soporte               | ✓                | Consumo de energía (max)                          | 58 W        |
| Relación de separación de GPON (máx.)           | 1:128            | Condiciones ambientales                           |             |
| Distancia lógica máxima (GPON)                  | 20000 m          | Intervalo de temperatura operativa                | 0 - 50 °C   |
| Lista de Control de Acceso (ACL)                | ✓                | Intervalo de temperatura de almacenaje            | -40 - 70 °C |
| Puertos e Interfaces                            |                  | Intervalo de humedad relativa para funcionamiento | 10 - 90%    |
| Puertos ascendentes                             | Gigabit Ethernet | Intervalo de humedad relativa durante almacenaje  | 5 - 90%     |
| Ethernet LAN (RJ-45) cantidad de puertos        | 2                | Peso y dimensiones                                |             |
| Número de puertos GPON                          | 4                | Ancho                                             | 440 mm      |
|                                                 |                  | Profundidad                                       | 180 mm      |
|                                                 |                  | Altura                                            | 44 mm       |



4897098683163



4897098683156



0840030703164



840030703164

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.