

TEST REPORT

Application No.: SHEM1912019492HS
Applicant: JIANGSU SAINTY MACHINERY IMP.& EXP. CO.,LTD
Address of Applicant: Building C, 21 Software Avenue, Nanjing, China
Manufacturer: JIANGSU SAINTY MACHINERY IMP.& EXP. CO.,LTD
Address of Manufacturer: Building C, 21 Software Avenue, Nanjing, China
Factory: JIANGSU SAINTY MACHINERY IMP.& EXP. CO.,LTD
Address of Factory: Building C, 21 Software Avenue, Nanjing, China
Equipment Under Test (EUT):
EUT Name: SCALE
Model No.: Refer to Page 2
Standard(s) : EN 55014-1:2017
 EN 55014-2:2015
Date of Receipt: 2019-12-06
Date of Test: 2019-12-10 to 2019-12-11
Date of Issue: 2019-12-20

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

The CE mark as shown below can be used, under the responsibility of the manufacturer, after completion of an EU Declaration of Conformity and compliance with all relevant EU Directives.

Parlam Zhan

Parlam Zhan
E&E Section Manager



The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.
Testing Center EMC Laboratory

NO. 588 West Jindu Road, Songjiang District, Shanghai, China 201612
中国·上海·松江区金都西路588号 邮编: 201612

t(86-21) 61915666 f(86-21) 61915678 www.sgsgroup.com.cn
t(86-21) 61915666 f(86-21) 61915678 e sgs.china@sgs.com



Model No:

SS-2001,SS-2002,SS-2003,SS-2004,SS-2005,SS-2006,SS-2007,SS-2008,SS-2009,SS-2010,SS-2011,SS-2012,SS-2013,SS-2014,SS-2015,SS-2016,SS-2017,SS-2018,SS-2019,SS-2020,SS-2021,SS-2022,SS-2023,SS-2024,SS-2025,SS-2026,SS-2027,SS-2028,SS-2029,SS-2030,SS-2031,SS-2032,SS-2033,SS-2034,SS-2035,SS-2036,SS-2037,SS-2038,SS-2039,SS-2040,SS-2041,SS-2042,SS-2043,SS-2044,SS-2045,SS-2046,SS-2047,SS-2048,SS-2049,SS-2050,SS-2051,SS-2052,SS-2053,SS-2054,SS-2055,SS-2056,SS-2057,SS-2058,SS-2059,SS-2060,SS-2061,SS-2062,SS-2063,SS-2064,SS-2065,SS-2066,SS-2067,SS-2068,SS-2069,SS-2070,SS-2071,SS-2072,SS-2073,SS-2074,SS-2075,SS-2076,SS-2077,SS-2078,SS-2079,SS-2080,SS-2081,SS-2082,SS-2083,SS-2084,SS-2085,SS-2086,SS-2087,SS-2088,SS-2089,SS-2090,SS-2091,SS-2092,SS-2093,SS-2094,SS-2095,SS-2096,SS-2097,SS-2098,SS-2099,SS-2100,SS-2101,SS-2102,SS-2103,SS-2104,SS-2105,SS-2106,SS-2107,SS-2108,SS-2109,SS-2110,SS-2111,SS-2112,SS-2113,SS-2114,SS-2115,SS-2116,SS-2117,SS-2118,SS-2119,SS-2120,SS-2121,SS-2122,SS-2123,SS-2124,SS-2125,SS-2126,SS-2127,SS-2128,SS-2129,SS-2200,SS-2201,SS-2202,SS-2203,SS-2204,SS-2205,SS-2206,SS-2207,SS-2208,SS-2209,SS-2210,SS-2211,SS-2212,SS-2213,SS-2214,SS-2215,SS-2216,SS-2217,SS-2218,SS-2219,SS-2220,SS-2221,SS-2222,SS-2223,SS-2224,SS-2225,SS-2226,SS-2227,SS-2228,SS-2229,SS-2300,SS-2301,SS-2302,SS-2303,SS-2304,SS-2305,SS-2306,SS-2307,SS-2308,SS-2309,SS-2310,SS-2311,SS-2312,SS-2313,SS-2314,SS-2315,SS-2316,SS-2317,SS-2318,SS-2319,SS-2320,SS-2321,SS-2322,SS-2323,SS-2324,SS-2325,SS-2326,SS-2327,SS-2328,SS-2329,SS-2330,SS-2331,SS-2332,SS-2333,SS-2334,SS-2335,SS-2336,SS-2337,SS-2338,SS-2339,SS-2340,SS-2341,SS-2342,SS-2343,SS-2344,SS-2345,SS-2346,SS-2347,SS-2348,SS-2349,SS-2400,SS-2401,SS-2402,SS-2403,SS-2404,SS-2405,SS-2406,SS-2407,SS-2408,SS-2409,SS-2410,SS-2411,SS-2412,SS-2413,SS-2414,SS-2415,SS-2416,SS-2417,SS-2418,SS-2419,SS-2420,SS-2421,SS-2422,SS-2423,SS-2424,SS-2425,SS-2426,SS-2427,SS-2428,SS-2429,SS-2430,SS-2431,SS-2432,SS-2433,SS-2434,SS-2435,SS-2436,SS-2437,SS-2438,SS-2439,SS-2440,SS-2441,SS-2442,SS-2443,SS-2444,SS-2445,SS-2446,SS-2447,SS-2448,SS-2449,SS-2450,SS-2451,SS-2452,SS-2453,SS-2454,SS-2455,SS-2456,SS-2457,SS-2458,SS-2459,SS-2460,SS-2461,SS-2462,SS-2463,SS-2464,SS-2465,SS-2466,SS-2467,SS-2468,SS-2469,SS-2480,SS-2481,SS-2482,SS-2483,SS-2484,SS-2485,SS-2486,SS-2487,SS-2488,SS-2489,SS-2500,SS-2501,SS-2502,SS-2503,SS-2504,SS-2505,SS-2506,SS-2507,SS-2508,SS-2509,SS-2510,SS-2511,SS-2512,SS-2513,SS-2514,SS-2515,SS-2516,SS-2517,SS-2518,SS-2519,SS-2600,SS-2601,SS-2602,SS-2603,SS-2604,SS-2605,SS-2606,SS-2607,SS-2608,SS-2609,SS-2610,SS-2611,SS-2612,SS-2613,SS-2614,SS-2615,SS-2616,SS-2617,SS-2618,SS-2619,SS-2700,SS-2701,SS-2702,SS-2703,SS-2704,SS-2705,SS-2706,SS-2707,SS-2708,SS-2709,SS-2710,SS-2800,SS-2801,SS-2802,SS-2803,SS-2804,SS-2805,SS-2806,SS-2807,SS-2808,SS-2809,SS-2810,SS-2811,SS-2812,SS-2813,SS-2814,SS-2815,SS-2816,SS-2817,SS-2818,SS-2819,SS-2820,,SS-2900,SS-2901,SS-2902,SS-2903,SS-2904,SS-2905,SS-2906,SS-2907,SS-2908,SS-2909,SS-2910,SS-2911,SS-2912



Revision Record			
Version	Description	Date	Remark
00	Original	2019-12-18	/
01	Updated § 4	2019-12-20	Amendment

Remark: The version 01 of the report had replaced the version 00 which was invalid.

Authorized for issue by:			
			
		Leo Xu / Project Engineer	
			
		Bruce Tang / Reviewer	

2 Test Summary

Emission Part				
Item	Standard	Method	Requirement	Result
Radiated Emissions (30MHz-1GHz)	EN 55014-1:2017	CISPR 16-2-3	N/A	Pass

N/A: Not applicable

Immunity Part				
Item	Standard	Method	Requirement	Result
Electrostatic Discharge	EN 55014-2:2015	EN 61000-4-2:2009	4kV Contact Discharge 8kV Air Discharge	Pass
Radiated Immunity (80MHz-1GHz)	EN 55014-2:2015	EN 61000-4-3:2006 +A1:2008+A2:2010	3V/m, 80%, 1kHz Amp. Mod.	Pass

N/A: Not applicable



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 DETAILS OF E.U.T.	5
4.2 DESCRIPTION OF SUPPORT UNITS	5
4.3 MEASUREMENT UNCERTAINTY	5
4.4 TEST LOCATION	5
4.5 TEST FACILITY	6
4.6 DEVIATION FROM STANDARDS	6
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
4.8 MONITORING OF EUT FOR ALL IMMUNITY TEST	6
5 EQUIPMENT LIST	7
6 EMISSION TEST RESULTS	8
6.1 RADIATED EMISSIONS (30MHZ-1GHZ)	8
7 IMMUNITY TEST RESULTS	11
7.1 PERFORMANCE CRITERIA DESCRIPTION IN EN 55014-2:2015	11
7.2 ELECTROSTATIC DISCHARGE	12
7.3 RADIATED IMMUNITY (80MHZ-1GHZ)	13
8 PHOTOGRAPHS	14
8.1 RADIATED EMISSIONS (30MHZ-1GHZ) TEST SETUP	14
8.2 ELECTROSTATIC DISCHARGE TEST SETUP	14
8.3 RADIATED IMMUNITY (80MHZ-1GHZ) TEST SETUP	15
8.4 EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)	16

4 General Information

4.1 Details of E.U.T.

Power supply: DC3V CR2032*1

4.2 Description of Support Units

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Conducted Emission at mains port using AMN	±2.6dB (9kHz to 150kHz)
		±2.3dB (150kHz to 30MHz)
2	Conducted Emission at mains port using VP	±1.9 dB (9kHz to 30MHz)
3	Conducted Emission at telecommunication port using AAN	±4.1 dB (150kHz to 30MHz)
4	Radiated Power	±3.0dB
5	Radiated emission	±4.4dB (30MHz-1GHz)
		±4.8dB (1GHz-6GHz)
		±5.2dB (6GHz-18GHz)

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **NVLAP (Certificate No. 201034-0)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

- **FCC –Designation Number: CN5033**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

IC Registration No.: 8617A-1. CAB identifier: CN0020.

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None

4.8 Monitoring of EUT for All Immunity Test

Visual: working status

5 Equipment List

Radiated Emissions (30MHz-1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI test receiver	Rohde & Schwarz	ESU40	SHEM051-1	2018-12-20	2019-12-19
CONTROLLER	INNCO	CO200	SHEM047-1	N/A	N/A
ANTENNA MAST	INNCO	MA400-EP	SHEM047-2	N/A	N/A
TURN DEVICE	INNCO	DE 3600-RH	SHEM047-3	N/A	N/A
Broadband UHF-VHF ANTENNA	SCHWARZBECK	VULB9168	SHEM048-1	2017-02-28	2020-02-27
Semi/Fully Anechoic	ST	11*6*6M	SHEM078-2	2017-07-22	2020-07-21
Low Amplifier	CLAVIO	BDLNA-0001-412010	SHEM164-1	2019-08-13	2020-08-12

Electrostatic Discharge					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Electrostatic Discharge Simulator	TESEQ	NSG 437	SHEM041-2	2019-08-13	2020-08-12

Radiated Immunity (80MHz-1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Signal generator	Rohde & Schwarz	SMJ100A	SHEM141-1	2019-08-13	2020-08-12
Power Meter	Rohde & Schwarz	NRP	SHEM057-1	2018-12-20	2019-12-19
Power meter sensor	Rohde & Schwarz	NRP-Z91	SHEM057-2	2018-12-20	2019-12-19
Antenna	SCHWARZBECK	STLP9128D	SHEM130-1	N/A	N/A
Amplifier	MILMEGA	AS0840-55-55	SHEM133-1	2018-12-20	2019-12-19
Power meter sensor	Rohde & Schwarz	NRP-Z22	SHEM136-1	2018-12-20	2019-12-19
ElectroMagnetic Field Probe	ETS-Lindgren	HI-6105	SHEM134-1	2018-12-11	2019-12-10
Semi/Fully Anechoic	ST	11*6*6M	SHEM078-2	2017-07-22	2020-07-21

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Digital pressure meter	YONGZHI	DYM3-01	SHEM082-1	2018-01-25	2021-01-24
Temperature&humidity recorder	ShangHai weather meter work	ZJ 1-2B	SHEM042-1~6	2019-09-16	2020-09-15
Digital Multimeter	FLUKE	17B	SHEM043-3	2019-09-02	2020-09-01
Autoformer regulator	Guangzhou bao de	TDGC2-5KVA	SHEM150-1	N/A	N/A
Multi-purpose tong tester	FLUKE	316	SHEM001-1	2018-12-20	2019-12-19

6 Emission Test Results

6.1 Radiated Emissions (30MHz-1GHz)

Test Requirement: EN 55014-1:2017

Test Method: CISPR 16-2-3

Frequency Range: 30MHz to 1GHz

Measurement Distance: 3m

Limit:

30MHz-230MHz 40 dB(μ V/m) quasi-peak

230MHz-1GHz 47 dB(μ V/m) quasi-peak

Detector: Peak for pre-scan (120kHz resolution bandwidth) 30M to 1000MHz


6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1020 mbar

Test mode a: Keep EUT measuring.


6.1.2 Test Setup Diagram



6.1.3 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.

Mode:a; Polarization:Horizontal



Antenna Polarity :HORIZONTAL


EUT/Project :19492HS

Test mode :a

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	55.415	37.54	13.37	0.54	42.33	9.12	40.00	-30.88	QP
2	109.796	47.09	10.05	1.21	42.30	16.05	40.00	-23.95	QP
3	140.835	38.73	12.54	1.38	42.25	10.40	40.00	-29.60	QP
4	222.170	42.47	9.64	1.96	42.14	11.93	40.00	-28.07	QP
5	815.968	35.54	22.40	4.40	41.95	20.39	47.00	-26.61	QP
6	982.620	35.01	24.00	4.57	41.17	22.41	47.00	-24.59	QP

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:a; Polarization:Vertical



Antenna Polarity :VERTICAL

EUT/Project :19492HS

Test mode :a

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	55.415	35.96	13.37	0.54	42.33	7.54	40.00	-32.46	QP
2	110.182	42.24	10.10	1.21	42.30	11.25	40.00	-28.75	QP
3	137.420	38.66	12.33	1.39	42.25	10.13	40.00	-29.87	QP
4	164.908	37.35	13.00	1.49	42.21	9.63	40.00	-30.37	QP
5	830.400	36.93	22.48	4.48	41.87	22.02	47.00	-24.98	QP
6	952.094	35.04	24.00	4.73	41.38	22.39	47.00	-24.61	QP

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

7 Immunity Test Results


7.1 Performance Criteria Description in EN 55014-2:2015

Criterion A	The apparatus shall continue to operate as intended during the test. No degradation of performance or loss of function is allowed below a performance level (or permissible loss of performance) specified by the manufacturer, when the apparatus is used as intended. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and from what the user may reasonably expect from the apparatus if used as intended.
Criterion B	The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level (or permissible loss of performance) specified by the manufacturer, when the apparatus is used as intended. During the test, degradation of performance is allowed, however. No change of actual operating state or stored data is allowed. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation and from what the user may reasonably expect from the apparatus if used as intended.
Criterion C	Temporary loss of function is allowed, provided the function is self recoverable or can be restored by the operation of the controls, or by any operation specified in the instructions for use.

7.2 Electrostatic Discharge

Test Requirement: EN 55014-2:2015
 Test Method: EN 61000-4-2:2009
 Performance Criterion: B
 Discharge Impedance: 330Ω/150pF
 Number of Discharge: Minimum 10 times at each test point
 Discharge Mode: Single Discharge
 Discharge Period: 1 second minimum

7.2.1 Test Setup Diagram



7.2.2 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1020 mbar

Test mode: a: Keep EUT measuring.

7.2.3 Test Results:

Observations: Test Point:

1. All insulated enclosure and seams.
2. All accessible metal parts of the enclosure.
3. All side

Discharge type	Level (kV)	Polarity	Test Point	Result / Observations
Air Discharge	8	+	1	A
Air Discharge	8	-	1	A
Contact Discharge	4	+	2	A
Contact Discharge	4	-	2	A
Horizontal Coupling	4	+	3	A
Horizontal Coupling	4	-	3	A
Vertical Coupling	4	+	3	A
Vertical Coupling	4	-	3	A


Results:

A: No degradation in the performance of the EUT was observed.

7.3 Radiated Immunity (80MHz-1GHz)

Test Requirement: EN 55014-2:2015
 Test Method: EN 61000-4-3:2006 +A1:2008+A2:2010
 Performance Criterion: A
 Frequency Range: 80MHz to 1GHz
 Antenna Polarisation: Vertical and Horizontal
 Modulation: 1kHz,80% Amp. Mod,1% increment

7.3.1 Test Setup Diagram



7.3.2 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1020 mbar

Test mode: a: Keep EUT measuring.

7.3.3 Test Results:

Frequency	Level (V/m)	EUT Face	Dwell time	Result / Observations
80MHz-1GHz	3	Front	2s	A
80MHz-1GHz	3	Back	2s	A
80MHz-1GHz	3	Left	2s	A
80MHz-1GHz	3	Right	2s	A

Results:


A: No degradation in the performance of the EUT was observed.

8 Photographs


8.1 Radiated Emissions (30MHz-1GHz) Test Setup





8.2 Electrostatic Discharge Test Setup







8.3 Radiated Immunity (80MHz-1GHz) Test Setup



8.4 EUT Constructional Details (EUT Photos)







- End of the Report -