


StarTech.com Adaptador Tarjeta PCI Express PCI-E 4 Puertos USB 3.0 (5Gbps) UASP 2 Canales de 5Gbps con Alimentación Molex SATA

Marca : StarTech.com

Código del producto: PEXUSB3S44V

Nombre del producto : Adaptador Tarjeta PCI Express PCI-E 4 Puertos USB 3.0 (5Gbps) UASP 2 Canales de 5Gbps con Alimentación Molex SATA

StarTech Adaptador Tarjeta PCI Express PCI-E 4 Puertos USB 3.0 (5Gbps) UASP 2 Canales de 5Gbps con Alimentación Molex SATA - Hub Interno (PEXUSB3S44V)
StarTech.com Adaptador Tarjeta PCI Express PCI-E 4 Puertos USB 3.0 (5Gbps) UASP 2 Canales de 5Gbps con Alimentación Molex SATA. Interfaz de host: PCIe, Interfaz de salida: USB 3.2 Gen 1 (3.1 Gen 1), Factor de forma de la tarjeta de expansión: Full-height / Low-profile. Color del producto: Negro, Longitud máxima del cable: 3 m. Circuito integrado: Renesas/NEC - μPD720202, Tasa de transferencia de datos (max): 20 Gbit/s. Sistema operativo Windows soportado: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10..., Sistema operativo de servidor soportado: Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows.... Ancho: 15 mm, Profundidad: 167 mm, Altura: 120 mm



Puertos e Interfaces		Requisitos del sistema		
Interfaz de host *	PCIe	Sistema operativo Windows soportado	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64	
Interfaz de salida *	USB 3.2 Gen 1 (3.1 Gen 1)			
Factor de forma de la tarjeta de expansión	Full-height / Low-profile			
Estándar de la tarjeta de expansión	PCIe 2.0			
Cantidad de puertos tipo A USB 3.2 Gen 1 (3.1 Gen 1)	4			
Conectores de poder (4 pin) periferales (Molex)	1			
Diseño		Sistema operativo Linux soportado	✓	
Interno *	✓			
Color del producto	Negro			
Longitud máxima del cable	3 m			
Características				
Circuito integrado	Renesas/NEC - μPD720202			
Tasa de transferencia de datos (max)	20 Gbit/s			
apoyo UASP	✓			
Condiciones ambientales				
Intervalo de temperatura operativa	0 - 50 °C			
Intervalo de temperatura de almacenaje	-20 - 60 °C			
Intervalo de humedad relativa para funcionamiento	5 - 85%			

Requisitos del sistema	
Sistema operativo de servidor soportado	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Detalles técnicos	
Certificados de conformidad	RoHS
Peso y dimensiones	
Ancho	15 mm
Profundidad	167 mm
Altura	120 mm
Peso	92 g
Empaquetado	
Controladores incluidos	✓
Manual de usuario	✓
Manual de usuario	✓
Ancho del paquete	211 mm
Profundidad del paquete	146 mm
Altura del paquete	41 mm
Peso del paquete	202 g
Datos logísticos	
Código de Sistema de Armomización (SA)	84733020
Cantidad por caja	40 pieza(s)
Ancho de la caja principal	444 mm
Longitud de la caja	425 mm
Alto de la caja principal	319 mm



0065030854627



065030854627



5054484566939

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.