

StarTech.com Tarjeta PCI Express de 2 Puertos USB 3.0 (5Gbps) SuperSpeed con UASP y Alimentación SATA - Adaptador Interno


Marca : StarTech.com

Código del producto: PEXUSB3S24

Nombre del producto : Tarjeta PCI Express de 2 Puertos USB 3.0 (5Gbps) SuperSpeed con UASP y Alimentación SATA - Adaptador Interno

- Suministra dos puertos USB 3.2 Gen 1 externos con soporte para UASP
- Soporta tasas de transferencia de datos de hasta 5 Gbps
- Cumple con la especificación PCI Express 2.0
- Conector opcional SATA de alimentación ofrece hasta 900 mA por puerto USB
- Soporta la especificación USB 1.2 de carga de baterías
- Totalmente compatible con las especificaciones para USB 3.2 Gen 1 rev 1.0 e Intel xHCI rev 1.0
- Retrocompatible con dispositivos USB 2.0 y USB 1.0/1.1
- Incluye un bracket de instalación de perfil bajo/altura media

StarTech Tarjeta PCI Express de 2 Puertos USB 3.0 (5Gbps) con UASP y Alimentación SATA - Adaptador Hub USB SuperSpeed Interno (PEXUSB3S24)



| Puertos e Interfaces                                 |                           | Requisitos del sistema                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
|------------------------------------------------------|---------------------------|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| Interfaz de host *                                   | PCIe                      | Sistema operativo Windows soportado     | Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64 |        |
| Interfaz de salida *                                 | USB 3.2 Gen 1 (3.1 Gen 1) |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
| Factor de forma de la tarjeta de expansión           | Perfil bajo               |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
| Estándar de la tarjeta de expansión                  | PCIe 2.0                  |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
| Cantidad de puertos tipo A USB 3.2 Gen 1 (3.1 Gen 1) | 2                         |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
| Diseño                                               |                           | Sistema operativo Linux soportado       | Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |        |
| Interno *                                            | ✓                         |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
| Color del producto                                   | Verde, Metálico           |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
| Certificación                                        | CE, FCC, TAA, REACH       |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
| Características                                      |                           |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
| Circuito integrado                                   | Renesas/NEC - μPD720202   |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
| Tasa de transferencia de datos (max)                 | 5 Gbit/s                  |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
| apoyo UASP                                           | ✓                         |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
| Condiciones ambientales                              |                           |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
| Intervalo de temperatura operativa                   | 5 - 50 °C                 |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
| Intervalo de temperatura de almacenaje               | -25 - 70 °C               | Sistema operativo Linux soportado       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | ✓      |
| Intervalo de humedad relativa para funcionamiento    | 20 - 80%                  | Sistema operativo de servidor soportado |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
| Peso y dimensiones                                   |                           |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |
| Ancho                                                |                           |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 18 mm  |
| Profundidad                                          |                           |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 65 mm  |
| Altura                                               |                           |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 120 mm |

| Peso y dimensiones                     |             |
|----------------------------------------|-------------|
| Peso                                   | 40 g        |
| Empaquetado                            |             |
| Soportes de montaje incluidos          | ✓           |
| Controladores incluidos                | ✓           |
| Manual de usuario                      | ✓           |
| Ancho del paquete                      | 143 mm      |
| Profundidad del paquete                | 175 mm      |
| Altura del paquete                     | 32 mm       |
| Peso del paquete                       | 130 g       |
| Datos logísticos                       |             |
| Código de Sistema de Armomización (SA) | 84733020    |
| Cantidad por caja                      | 60 pieza(s) |
| Ancho de la caja principal             | 382 mm      |
| Longitud de la caja                    | 498 mm      |
| Alto de la caja principal              | 318 mm      |



0065030855587



065030855587



0172304231388



172304231388

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.