

APC Smart-UPS 1500VA LCD RM - UPS (rack-mountable)

AC 220/230/240 V - 1000 Watt - 1500 VA - RS-232 - USB - output connectors: 4 - 2U - black - with APC SmartConnect - for P/N: AR106V - AR106VI - AR112SH6 - AR3006 - AR3006SP - AR3103 - AR3103SP - AR3106 - AR3106SP

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMT1500RMI2UC
EAN/UPC	0731304333005

Description

Intuitive LCD interface provides clear and accurate information in multiple languages with the ability to configure the UPS locally with easy to use navigation keys.
Predictive replace battery date dynamically provides the month and year when battery replacement is recommended to aide in long term maintenance planning.

Main features

Product Description	APC Smart-UPS 1500VA LCD RM - UPS - 1000 Watt - 1500 VA - with APC SmartConnect
Device Type	UPS - rack-mountable
Rack Size	2U
Weight	26.1 kg
Input Voltage	AC 220/230/240 V
Output Voltage	AC 220/230/240 V
Power Capacity	1000 Watt / 1500 VA
Input Connectors	Power IEC 60320 C14
Output connectors	4 x power IEC 60320 C13
Battery	Lead Acid
Run Time (Up To)	7.2 min at full load
Networking	RS-232, USB
Remote Management Protocol	SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, SSH, SSH-2
Colour	Black
Dimensions (WxDxH)	43.2 cm x 47.7 cm x 8.6 cm
Environmental Standards	ENERGY STAR
Bundled with	APC SmartConnect
Designed For	P/N: AR106V, AR106VI, AR112SH6, AR3003SP, AR3006, AR3006SP, AR3103, AR3103SP, AR3106, AR3106SP, AR3140G, AR3340G, AR3355W, AR3357X674, AR4018IX429, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432,

	AR4018X429, AR4024IX431, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4038IX432, NBWL0356A

Extended details

	General
Device Type	UPS - rack-mountable
Height (Rack Units)	2U
Colour	Black
Bundled with	APC SmartConnect
	Power Device
UPS Technology	Line interactive
Input Voltage	AC 220/230/240 V
Input Voltage Range	AC 160 - 286 V
Input Voltage Range (Adjustable)	AC 151 - 302 V
Frequency Provided	57 - 63 Hz
Frequency Required	50/60 Hz
Input Connectors	Power IEC 60320 C14
Power Output Connectors Details	4 x power IEC 60320 C13
Output Voltage	AC 220/230/240 V 57 - 63 Hz
Power Capacity	1000 Watt / 1500 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	459 Joules
Circuit Protection	Circuit breaker
	Battery
Technology	Lead Acid
Run Time (Up To)	7.2 min at full load
Recharge Time	3 hours
Transfer Time	6 ms
Features	Maintenance free, sealed, leak-proof
	Networking
Remote Management Interface	RS-232, USB
Remote Management Protocol	SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, SSH, SSH-2
	Expansion / Connectivity
Interfaces	1 x management (USB) - 4 pin USB Type B ¦ 1 x management (RS-232) - RJ-45
Expansion Slots	1 SmartSlot
	Miscellaneous
Cables Included	Serial cable ¦ USB cable
Rack Mounting Kit	Included
Features	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), LED indicators
Compliant Standards	CSA, UL 1778, VDE, IEC 62040-2, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1

	Software / System Requirements
Software Included	APC PowerChute Business Edition
	Environmental Standards
ENERGY STAR	Yes
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years ¦ Limited warranty - batteries - 2 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	46 dBA
	Dimensions & Weight
Width	43.2 cm
Depth	47.7 cm
Height	8.6 cm
Weight	26.1 kg
	Dimensions & Weight (Shipping)
Shipping Width	59.4 cm
Shipping Depth	60.3 cm
Shipping Height	25.1 cm
Shipping Weight	31.91 kg
	Compatibility Information
Designed For	P/N: ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC1021, ACDC2513, ACF001, ACF002, ACF003, ACF101BLK, ACF102BLK, ACF201BLK, ACF400, ACF600, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR100, AR100HD, AR106V, AR106VI, AR112SH6, AR202, AR203A, AR204A, AR2101, AR2102BLK, AR2144BLK, AR2145BLK, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR2900, AR2901, AR3000, AR3003SP, AR3006, AR3006SP, AR3100, AR3100G, AR3100SP, AR3100SP1, AR3100SP2, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3103, AR3103SP, AR3104, AR3104SP1, AR3105, AR3105SP, AR3105W, AR3106, AR3106SP, AR3107, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140, AR3140G, AR3140W, AR3150, AR3150SP, AR3150SP1, AR3150SP2, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3200, AR3300, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3357X674, AR4018, AR4018A, AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A, AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429,

AR4038IX431, AR4038IX432, AR4038X429, AR4038X432, AR7007, AR7050, AR7057, NBWL0356A

Technical data © CNET Content Solutions. Subject to technical modifications and errors.