

APC Smart-UPS C SMC1500I-2UC - UPS (rack-mountable)

AC 220/230/240 V - 900 Watt - 1500 VA - RS-232 - USB - output connectors: 4 - 2U - black - with APC SmartConnect

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMC1500I-2UC
EAN/UPC	0731304332954



Description

Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Main features

Product Description	APC Smart-UPS C SMC1500I-2UC - UPS - 900 Watt - 1500 VA - with APC SmartConnect
Device Type	UPS - rack-mountable
Rack Size	2U
Weight	28.64 kg
Input Voltage	AC 220/230/240 V
Output Voltage	AC 230 V $\pm$ 5%
Power Capacity	900 Watt / 1500 VA
Input Connectors	1 x power IEC 60320 C14
Output connectors	4 x power IEC 60320 C13 2 x IEC jumper
Battery	Lead Acid
Batteries Qty	1
Run Time (Up To)	10.1 min at full load
Networking	RS-232, USB
Colour	Black
Dimensions (WxDxH)	43.2 cm x 47.7 cm x 8.6 cm
Bundled with	APC SmartConnect

Extended details

General	
Device Type	UPS - rack-mountable
Height (Rack Units)	2U
Colour	Black
Bundled with	APC SmartConnect

	Power Device
UPS Technology	Line interactive
Input Voltage	AC 220/230/240 V
Input Voltage Range	AC 180 - 287 V
Input Voltage Range (Adjustable)	AC 170 - 300 V
Frequency Provided	50/60 Hz $\pm$ 3Hz
Frequency Required	50/60 Hz $\pm$ 3Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	4 x power IEC 60320 C13 2 x IEC jumper
Output Voltage	AC 230 V $\pm$ 5% - 50/60 Hz
Power Capacity	900 Watt / 1500 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	459 Joules
Circuit Protection	Circuit breaker
	Battery
Quantity	1
Technology	Lead Acid
Run Time (Up To)	10.1 min at full load 25 min at half load 173 min at 50 Watts 107 min at 100 Watts 59 min at 200 Watts 39.2 min at 300 Watts 28.6 min at 400 Watts 22.1 min at 500 Watts 17.6 min at 600 Watts 14.4 min at 700 Watts 12 min at 800 Watts 10.1 min at 900 Watts
Recharge Time	3 hours
Features	Maintenance free
	Networking
Remote Management Interface	RS-232, USB
	Expansion / Connectivity
Interfaces	1 x management (USB) - 4 pin USB Type B 1 x serial - RJ-45
	Miscellaneous
Cables Included	Serial cable - external USB cable - external
Features	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), cold-start function, automatic shut down reset, automatic self-test, hot-swappable batteries
Compliant Standards	CSA, C-Tick, GOST, UL 1778, VDE
	Software / System Requirements
Software Included	APC PowerChute Business Edition
	Manufacturer Warranty
Service & Support	Limited warranty - parts and labour - 2 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C

Humidity Range Operating	0 - 95%
Sound Emission	46 dBA
Dimensions & Weight	
Width	43.2 cm
Depth	47.7 cm
Height	8.6 cm
Weight	28.64 kg
Dimensions & Weight (Shipping)	
Shipping Width	59.4 cm
Shipping Depth	60.3 cm
Shipping Height	25.1 cm
Shipping Weight	31.91 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.