



Dahua Technology PFS3125-24ET-190 switch No administrado L2 Fast Ethernet (10/100) Energía sobre Ethernet (PoE) Negro

Marca : Dahua Technology

Código del producto: PFS3125-24ET-190

Nombre del producto : PFS3125-24ET-190

Dahua Technology PFS3125-24ET-190. Tipo de interruptor: No administrado, Capa del interruptor: L2. Puertos tipo básico de conmutación RJ-45 Ethernet: Fast Ethernet (10/100), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 24. Bidireccional completo (Full duplex). Tabla de direcciones MAC: 4000 entradas, Capacidad de conmutación: 6,8 Gbit/s. Estándares de red: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Energía sobre Ethernet (PoE)

Características de administración		Transmisión de datos	
Tipo de interruptor *	No administrado	Tabla de direcciones MAC *	4000 entradas
Capa del interruptor	L2	Guardar y remitir	✓
Puertos e Interfaces		Diseño	
Cantidad de puertos básicos de conmutación RJ-45 Ethernet *	24	Color del producto	Negro
Puertos tipo básico de conmutación RJ-45 Ethernet *	Fast Ethernet (10/100)	Material de la carcasa	Metal
Cantidad de puertos Fast Ethernet (cobre)	24	Indicadores LED	✓
Combo SFP Cantidad de puertos	1	Control de energía	
Conexión		Voltaje de entrada AC	100 - 240 V
Estándares de red *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Frecuencia de entrada AC	50 - 60 Hz
Soporte 10G *	✗	Alimentación a través de Ethernet (PoE)	
Tecnología de cableado ethernet de cobre	10BASE-T, 100BASE-TX, 1000BASE-T	Energía sobre Ethernet (PoE) *	✓
Bidireccional completo (Full duplex)	✓	Alimentación mediante Ethernet Plus (PoE +) Cantidad de puertos	24
Soporte de control de flujo	✓	Potencia a través de Ethernet (PoE) Presupuesto	190 W
Auto MDI / MDI-X	✓	Condiciones ambientales	
Admite dirección MAC auto-learning	✓	Intervalo de temperatura operativa	0 - 45 °C
Admite dirección MAC auto-aging	✓	Intervalo de temperatura de almacenaje	-40 - 70 °C
Soporte VLAN	✓	Intervalo de humedad relativa para funcionamiento	10 - 90%
Transmisión de datos		Intervalo de humedad relativa durante almacenaje	5 - 90%
Capacidad de conmutación *	6,8 Gbit/s	Peso y dimensiones	
Tasa de reenvío	5,06 Mpps	Ancho	340 mm
		Profundidad	200 mm
		Altura	43 mm



6939554955686

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.