



TP-Link EAP223 V1 867 Mbit/s Blanco Energía sobre Ethernet (PoE)

Marca : TP-Link

Código del producto: EAP223

Nombre del producto : EAP223 V1

TP-Link EAP223 V1. 2,4 GHz, 5 GHz, Rango máximo de transferencia de datos: 867 Mbit/s. Algoritmos de seguridad soportados: SSID. Energía sobre Ethernet (PoE). Color del producto: Blanco



Características		Control de energía	
2,4 GHz *	✓	Energía sobre Ethernet (PoE) *	✓
5 GHz *	✓	Compatible con tipo de PoE (Power over Ethernet, Alimentación a través de Ethernet)	Active PoE, Passive PoE
6 GHz *	✗	Voltaje de salida	48 V
Rango máximo de transferencia de datos *	867 Mbit/s	Consumo energético	9,7 W
Velocidad máxima de transferencia de datos (2,4 GHz)	450 Mbit/s	Diseño	
Velocidad máxima de transferencia de datos (5 GHz)	867 Mbit/s	Ubicación *	Techo, Pared
Estándares de red	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Color del producto *	Blanco
Selección automática de canal	✓	Botón de restaurar	✓
Escáner automático de canales	✓	Indicadores LED	Poder
MIMO	✓	Antena	
Tipo MIMO	Multi User MIMO	Tipo de antena *	Interno
Wi-Fi Multimedia (WMM)/(WME)	✓	Tipo de dirección de la antena	Omni-direccional
Soporte VLAN	✓	Cantidad de antenas	3
Limitar tasa	✓	Desempeño	
Aislamiento inalámbrico	✓	Sistemas operativos compatibles	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux
Band steering (optimización de rendimiento)	✓	Aprobaciones reguladoras	
Calidad de servicio (QoS) soporte	✓	Certificación	CE, FCC, RoHS
Potencia de transmisión (CE)	20, 23 dbm	Peso y dimensiones	
Potencia de transmisión (FCC)	24, 22 dbm	Ancho	205,5 mm
Seguridad		Profundidad	181,5 mm
Algoritmos de seguridad soportados *	SSID	Altura	37,1 mm
MAC, filtro de direcciones	✓	Contenido del embalaje	
		Cantidad por paquete	1 pieza(s)

Seguridad		Contenido del embalaje	
Número de SSID admitidos	15	Cables incluidos	Corriente alterna
Características de administración		Kit de montaje	✓
Administración basada en web	✓	Guía de configuración rápida	✓
Syslog	✓	Condiciones ambientales	
Plataforma de gestión	Omada	Intervalo de humedad relativa para funcionamiento	10 - 90%
Puertos e Interfaces		Intervalo de temperatura operativa	0 - 40 °C
Ethernet LAN (RJ-45) cantidad de puertos *	1	Intervalo de temperatura de almacenaje	-40 - 70 °C
		Intervalo de humedad relativa durante almacenaje	5 - 90%



4895252500509



0840030704277



840030704277

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.