



**AISENS A145-0325 cable de red Gris 0,5 m Cat6a U/UTP (UTP)**

**Marca :** AISENS **Código del producto:** A145-0325

**Nombre del producto :** A145-0325

Cable de red latiguillo RJ-45, LSZH, Cat6A, 500 MHz UTP, AWG24, 10G, 0.5m, Gris

AISENS A145-0325 cable de red Gris 0,5 m Cat6a U/UTP (UTP):

AISENS® – Cable de red latiguillo RJ45 LSZH CAT.6A UTP AWG24 100% cobre con conector RJ45 en ambos extremos, 0.5 metros | Conmutador/router/módem/panel de conexiones/punto de acceso/campos de conexión

AISENS A145-0325. Longitud de cable: 0,5 m, Cable estándar: Cat6a, Blindaje de cable: U/UTP (UTP), Conector 1: RJ-45, Conector 2: RJ-45, Velocidad de transferencia de datos: 10000 Mbit/s, Color del producto: Gris



| Características                     |                                                        | Características                 |                                                                                                                                                                                  |
|-------------------------------------|--------------------------------------------------------|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Color del producto *                | Gris                                                   | Funda protectora para conector  | ✓                                                                                                                                                                                |
| Longitud de cable *                 | 0,5 m                                                  | Conectar y usar (Plug and Play) | ✓                                                                                                                                                                                |
| Cable estándar *                    | Cat6a                                                  | Sostenibilidad                  |                                                                                                                                                                                  |
| Blindaje de cable *                 | U/UTP (UTP)                                            | No contiene                     | Halógeno                                                                                                                                                                         |
| Conector 1 *                        | RJ-45                                                  | Aprobaciones reguladoras        |                                                                                                                                                                                  |
| Conector 2 *                        | RJ-45                                                  | Certificados de conformidad     | RoHS                                                                                                                                                                             |
| Género del conector 1 *             | Macho                                                  | Certificación                   | ANSI / TIA / EIA 568-B-1, CAT6A, ISO / IEC 11801 CLASE E (2nd Edition), CENELEC EN 50173-1, IEC 61156-5, CENELEC EN 50288-6-1, IEC 61156-6, CENELEC EN 50288-6-2, IEC 60332-1-2. |
| Género del conector 2 *             | Macho                                                  |                                 |                                                                                                                                                                                  |
| Material de chaqueta                | Libre de halógenos (LSZH)                              |                                 |                                                                                                                                                                                  |
| Material del conductor              | Cobre sin oxígeno                                      | Contenido del embalaje          |                                                                                                                                                                                  |
| Tecnología de cableado              | 10Base-T(X)                                            | Cantidad por paquete            | 1 pieza(s)                                                                                                                                                                       |
| Tipo de interfaz ethernet           | 10 Gigabit Ethernet, Ethernet rápido, Gigabit Ethernet | Empaquetado                     |                                                                                                                                                                                  |
| AWG calibre del cable               | 24                                                     | Ancho del paquete               | 120 mm                                                                                                                                                                           |
| Velocidad de transferencia de datos | 10000 Mbit/s                                           | Profundidad del paquete         | 5 mm                                                                                                                                                                             |
| Frecuencia                          | 500 MHz                                                | Altura del paquete              | 160 mm                                                                                                                                                                           |
|                                     |                                                        | Peso del paquete                | 28 g                                                                                                                                                                             |



8436574703788

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.