



D-Link DUB-H7 USB 2.0 Type-B 480 Mbit/s Negro

Marca : D-Link

Código del producto: DUB-H7/B

Nombre del producto : DUB-H7

D-Link DUB-H7. Interfaz de host: USB 2.0 Type-B, Interfaces de concentradores: USB 2.0. Velocidad de transferencia de datos: 480 Mbit/s, Color del producto: Negro, Certificación: FCC, CE, C-Tick, VCCI, IC, RoHS. Voltaje de entrada: 5 DC, Corriente de entrada: 3 DC, Voltaje de salida: 5 V. Sistema operativo Windows soportado: Windows 10, Windows 7, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium,..., Sistema operativo MAC soportado: Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14..., Requisitos mínimos del sistema: USB. Ancho: 57 mm, Profundidad: 99 mm, Altura: 25 mm



Puertos e Interfaces		Condiciones ambientales	
Interfaz de host *	USB 2.0 Type-B	Intervalo de temperatura operativa	0 - 40 °C
Interfaces de concentradores *	USB 2.0	Intervalo de temperatura de almacenaje	-20 - 60 °C
Cantidad de puertos USB 2.0	7	Intervalo de humedad relativa para funcionamiento	10 - 90%
Puertos de entrada y salida (E/S)	7x downstream USB Type A Ports 1x upstream USB Type B Port	Intervalo de humedad relativa durante almacenaje	5 - 95%
Cantidad de puertos *	7	Datos logísticos	
Tarjeta de lectura integrada	✗	Peso bruto del palé (en avión)	208,8 kg
Enchufe de entrada de CC	✓	Número de cajas de cartón por palé (en avión)	36 pieza(s)
Características		Cantidad por palé (en avión)	360 pieza(s)
Velocidad de transferencia de datos *	480 Mbit/s	Altura del palé (en avión)	114 cm
Color del producto	Negro	Peso bruto del palé (en barco)	347,5 kg
Indicadores LED	✓	Número de cajas de cartón por palé (en barco)	63 pieza(s)
Conectar y usar (Plug and Play)	✓	Cantidad por palé (en barco)	630 pieza(s)
Certificación	FCC, CE, C-Tick, VCCI, IC, RoHS	Altura del palé (en barco)	193 cm
Control de energía		Anchura del palé	110 cm
Voltaje de entrada	5 DC	Longitud del palé	120 cm
Corriente de entrada	3 DC	Anchura de la caja de envío	31,4 cm
Voltaje de salida	5 V	Longitud del contenedor de envío	36 cm
Corriente de salida	2,4 A	Código de Sistema de Armomización (SA)	84719000
		Altura de la caja de envío	25,3 cm
		Peso de la caja de envío	5,18 kg
		Cantidad por caja de envío	10 pieza(s)
		Peso neto del envase de envío	2,6 kg
Otras características			
Interfaz		USB, OHCI, EHCI	
Seguridad		CE, FCC Class B, VCCI, UL	
Compatible con Mac		✓	
Dimensiones (Ancho x Profundidad x Altura)		99,6 x 59,5 x 25,7 mm	
Requisitos de energía		12.6W, 3 A @ 5 VDC	

Requisitos del sistema	
Sistema operativo Windows soportado	Windows 10, Windows 7, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Sistema operativo MAC soportado	Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.7.5 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Mac OS X 14.0 Sonoma
Sistema operativo Linux soportado	✓
Requisitos mínimos del sistema	USB
Sistemas operativos compatibles	Windows XP/ME/2000/98SE Mac OS X 10.1 or later

Peso y dimensiones	
Ancho	57 mm
Profundidad	99 mm
Altura	25 mm
Peso	85 g

Empaquetado	
Ancho del paquete	150 mm
Profundidad del paquete	225 mm
Altura del paquete	68 mm
Peso del paquete	477,5 g



0790069252372



790069252372



0790069252389



790069252389



0790069252396



790069252396

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.