ASUS ZenScreen MB166C - LED monitor

15.6" - portable - 1920 x 1080 Full HD (1080p) @ 60 Hz - IPS - 250 cd/m² - 800:1 - 5 ms - USB-C



Group	Flat Screens
Manufacturer	ASUS
Manufacturer item no.	90LM07D3-B01170
EAN/UPC	4711081273981

Description

ASUS ZenScreen MB166C - LED monitor - 15.6" - portable - 1920 x 1080 Full HD (1080p) @ 60 Hz - IPS - 250 cd/m² - 800:1 - 5 ms - USB-C

Main features

Product Description	ASUS ZenScreen MB166C - LED monitor - Full HD (1080p) - 15.6"
Device Type	LED-backlit LCD monitor - 15.6"
Energy Class	Class B
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.179 mm
Brightness	250 cd/m²
Contrast Ratio	800:1 / 100000000:1 (dynamic)
Response Time	5 ms (grey-to-grey)
Colour Support	262,000 colours
Input Connectors	USB-C
Screen Coating	Anti-glare
Voltage	AC 100-240 V (50/60 Hz)
Dimensions (WxDxH) - without stand	36.014 cm x 1.18 cm x 22.564 cm
Weight	780 g
Compliant Standards	TUV Rheinland Low Blue Light Certification, TUV Rheinland Flicker Free Certification

Extended details

	General
Display Type	LED-backlit LCD monitor / TFT active matrix

Energy Class	Class B
Diagonal Size	15.6"
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.179 mm
Brightness	250 cd/m²
Contrast Ratio	800:1 / 100000000:1 (dynamic)
Colour Support	262,000 colours
Response Time	5 ms (grey-to-grey)
Vertical Refresh Rate	60 Hz
Horizontal Refresh Rate	24 - 83 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare
Backlight Technology	LED backlight
Features	HDCP, ASUS Splendid Video Intelligence Technology, Trace Free Technology, ASUS QuickFit Virtual Scale, ASUS GamePlus, Low Blue Light Mode, Flicker Free technology, ASUS EyeCare Technology, Colour Temperature Selection, Display Widget, tripod socket
Dimensions (WxDxH)	36.014 cm x 1.18 cm x 22.564 cm - without stand
Weight	780 g
	Connectivity
Interfaces	USB-C
	Miscellaneous
Compliant Standards	TUV Rheinland Low Blue Light Certification, TUV Rheinland Flicker Free Certification
	Power
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption SDR (On mode)	6 kWh/1000h
Power Consumption (Typical)	8 Watt
Power Consumption Stand by	0.5 Watt

Power Consumption (Off Mode)	0.3 Watt
	Dimensions & Weight (Shipping)
Shipping Width	43.4 cm
Shipping Depth	7.6 cm
Shipping Height	29 cm
Shipping Weight	1.7 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.