

Eaton 9PX 1000i RT2U Netpack - UPS (rack-mountable / external)

AC 200/208/220/230/240 V - 1000 Watt - 1000 VA - RS-232 - USB - Ethernet 10/100/1000 - output connectors: 8 - PFC - 2U

Group	Power Supply
Manufacturer	Eaton
Manufacturer item no.	9PX1000IRTN



Description

As an industry professional, and because of rising energy costs and the business need for energy-efficient performance, you'll be looking for ways to reduce costs and consumption. The Eaton 9PX UPS enables you to secure all your mission-critical applications, giving you the reductions in energy usage and costs you need. Essentially, the Eaton 9PX UPS gives you the chance to optimize power density and minimize capital and operating expenditure, along with the assurance that, should the power go down, critical processes will be maintained in your IT infrastructures and other applications.

Main features

Product Description	Eaton 9PX 1000i RT2U Netpack - UPS - 1000 Watt - 1000 VA
Device Type	UPS - Power Factor Correction (PFC) - rack-mountable / external
Rack Size	2U
Weight	17.4 kg
Input Voltage	AC 200/208/220/230/240 V
Output Voltage	AC 200/208/220/230/240 V
Power Capacity	1000 Watt / 1000 VA
Input Connectors	1 x power IEC 60320 C14
Output connectors	Power IEC 60320 C14 ; 8 x power IEC 60320 C13
Networking	RS-232, USB, Ethernet 10/100/1000
Dimensions (WxDxH)	44 cm x 45 cm x 8.65 cm
Environmental Standards	ENERGY STAR

Extended details

	General
Device Type	UPS - Power Factor Correction (PFC) - rack-mountable / external
Height (Rack Units)	2U
	Power Device
UPS Technology	On-line
Input Voltage	AC 200/208/220/230/240 V
Input Voltage Range	AC 176 - 276 V

Frequency Required	40 - 70 Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	Power IEC 60320 C14 8 x power IEC 60320 C13
Output Voltage	AC 200/208/220/230/240 V
Power Capacity	1000 Watt / 1000 VA
Efficiency	98%
	Battery
Run Time (Up To)	28 min at 300 Watts 16 min at 500 Watts 9 min at 800 Watts
	Networking
Remote Management Interface	RS-232, USB, Ethernet 10/100/1000
	Expansion / Connectivity
Interfaces	1 x management (USB) 1 x management (RS-232) 1 x management (Gigabit Ethernet) - RJ-45
Expansion Slots	1 (total) / 0 (free) x Expansion Slot
	Miscellaneous
Features	Audible alarm, LCD display, internal bypass, overload protection, cold-start function
Compliant Standards	FCC Class B certified, TUV, CISPR 22 Class B, UL 1778, CB, IEC 62040-2, cULus, CSA 22.2, KC, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1
	Software / System Requirements
Software Included	Intelligent Power Software Suite
	Environmental Standards
ENERGY STAR	Yes
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years Limited warranty - batteries - 2 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Sound Emission	35 dBA
	Dimensions & Weight
Width	44 cm
Depth	45 cm
Height	8.65 cm
Weight	17.4 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.