

Product Specifications

# E10G18-T1



## Hardware Specifications

General	
Host Bus Interface	PCIe 3.0 x4
Bracket Height	Low Profile and Full Height
Size (Height x Width x Depth)	86.0 mm x 68.1 mm x 13.6 mm
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 60°C (-5°F to 140°F)
Relative Humidity	5% to 95% RH
Warranty	5 Years
Notes	The warranty period starts from the purchase date as stated on your purchase receipt. ( <a href="#">Learn more</a> )

Network	
IEEE Specification Compliance	<ul style="list-style-type: none"><li>• IEEE 802.3x Flow Control</li><li>• IEEE 802.3u Fast Ethernet</li><li>• IEEE 802.3ab Gigabit Ethernet</li><li>• IEEE 802.3bz 2.5Gbps / 5Gbps Ethernet</li><li>• IEEE 802.3an 10Gbps Ethernet</li></ul>
Data Transfer Rates	10 Gbps
Network Operation Mode	Full Duplex
Supported Features	<ul style="list-style-type: none"><li>• 9 KB Jumbo Frame</li><li>• TCP/UDP/IP Checksum Offloading</li><li>• Auto-negotiation between 100Mb/s, 1Gb/s, 2.5Gb/s, 5Gb/s, and 10Gb/s</li></ul>

## Compatibility

Applied Models
----------------

- FS series:FS6400, FS3600, FS3400, FS3017, FS2017, FS3410, FS2500
- SA series:SA3600, SA3400, SA6400, SA3200D
- UC series:UC3200
- 22 series:RS822RP+, RS822+, DS3622xs+, DS2422+
- 21 series:RS4021xs+, RS3621xs+, RS3621RPxs, RS2821RP+, RS2421RP+, RS2421+, RS1221RP+, RS1221+, DS1821+, DS1621xs+, DS1621+
- 20 series:RS820RP+, RS820+
- 19 series:RS1619xs+, RS1219+, DS2419+II
- 18 series:RS3618xs, RS2818RP+, RS2418RP+, RS2418+, RS818RP+, RS818+
- 17 series:RS18017xs+, RS4017xs+, RS3617xs+, RS3617RPxs, RS3617xs, DS3617xsII
- 16 series:RS18016xs+
- 15 series:RC18015xs+
- 14 series:RS3614xs+, RS3614RPxs, RS3614xs
- 13 series:RS10613xs+, RS3413xs+
- 12 series:RS3412RPxs, RS3412xs
- 11 series:RS3411RPxs, RS3411xs

---

Notes

DSM version requirement: 6.2-23739-2 onward (or 6.1-15284-2 onward with DSM 6.1)

---