

MPN: S-6UTP-05Y

Ultra Slim CAT6 U/UTP CU LSZH Ethernet Cable Yellow 5m

The ProXtend Ultra Slim CAT6 U/UTP CU ethernet cables are produced with 99.9% pure copper strands and an AWG of 28 to ensure the absolute best performance. The outer jacket of the cable is made from LSZH (Low Smoke Zero Halogen) ensuring low amounts of smoke, toxic fumes, and no acid gasses in case of a fire. The cable is reinforced with strain relief and a tangle free latch allowing for secure installation. The 3.6mm ultra slim form of the cable makes it more flexible and ensures a better air flow and cooling performance in complex network systems. Plated with 50"U gold, the connector provides more durability and a higher quality transmission rate. A 50"U gold connector can deliver up to 4x more throughput than a standard metal connector. 50"U is the thickest available and most optimal gold plating standard.

All ProXtend Ultra Slim CAT6 U/UTP CU ethernet cables support PoE++.

Supporting a variety of cable standards, lengths and shieldings, ProXtend is your one stop shop for ethernet cables ensuring that you are always able to find a cable that best suits your network requirements.



Caractéristiques

Caractéristiques	Blindage du câble	U/UTP (UTP)
	Câble standard	Cat6
	Connecteur 1	RJ45
	Connecteur 2	RJ45
	Contacts du connecteur de placage	Or
	Couleur du produit	Jaune
	Genre de connecteur 1	Mâle
	Genre de connecteur 2	Mâle
	Longueur de câble	5 m
	Matériau conducteur	Cuivre
	Matériau du manteau	LSZH (Low smoke zero halogen)
	Plug and Play	Oui
	Standards réseau	IEEE 802.3af
	Taille des fils AWG	28
	Taux de transfert de données	1000 Mbit/s
	Technologie de câblage	10/100Base-T(X)
	Type de conducteur	Gainé
Certificat	Certification	REACH, RoHS, CE
Conditions environnementales	Température d'opération	-20 - 60 °C
	Température hors fonctionnement	0 - 50 °C
Détails techniques	Certificats de conformité	RoHS
	Certificats de durabilité	RoHS
Informations sur	Manuel d'utilisation	Non

l'emballage

Quantité	1 pièce(s)
-----------------	------------

Poids et dimensions

Diamètre extérieur	3,6 mm
---------------------------	--------

Vendor information

Brand Name	ProXtend
-------------------	----------

Warranty	30 Année (s)
-----------------	--------------

Autres photos

