



APC Smart-UPS SMT1500IC - UPS

AC 220/230/240 V - 1000 Watt - 1500 VA - RS-232 - USB - output connectors: 8
- black - with APC SmartConnect

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMT1500IC
EAN/UPC	0731304332992

Description

Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Main features

Product Description	APC Smart-UPS SMT1500IC - UPS - 1000 Watt - 1500 VA - with APC SmartConnect
Device Type	UPS - external
Weight	24.09 kg
Input Voltage	AC 220/230/240 V
Output Voltage	AC 230 V $\pm$ 5%
Power Capacity	1000 Watt / 1500 VA
Input Connectors	1 x power IEC 60320 C14
Output connectors	8 x power IEC 60320 C13 2 x IEC jumper
Battery	Lead Acid
Batteries Qty	1
Run Time (Up To)	6.5 min at full load
Networking	RS-232, USB
Colour	Black
Dimensions (WxDxH)	17.1 cm x 43.9 cm x 21.9 cm
Bundled with	APC SmartConnect

Extended details

General	
Device Type	UPS - external
Colour	Black
Bundled with	APC SmartConnect
Power Device	



UPS Technology	Line interactive
Input Voltage	AC 220/230/240 V
Input Voltage Range	AC 160 - 286 V
Input Voltage Range (Adjustable)	AC 151 - 302 V
Frequency Provided	50/60 Hz $\pm$ 3Hz
Frequency Required	50/60 Hz $\pm$ 3Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	8 x power IEC 60320 C13 2 x IEC jumper
Output Voltage	AC 230 V $\pm$ 5% - 50/60 Hz
Power Capacity	1000 Watt / 1500 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	459 Joules
Circuit Protection	Circuit breaker
Battery	
Quantity	1
Technology	Lead Acid
Run Time (Up To)	6.5 min at full load 23.1 min at half load 301 min at 50 Watts 172 min at 100 Watts 84 min at 200 Watts 50.6 min at 300 Watts 33.3 min at 400 Watts 23.1 min at 500 Watts 16.6 min at 600 Watts 12.4 min at 700 Watts 9.6 min at 800 Watts 7.7 min at 900 Watts 6.5 min at 1000 Watts
Recharge Time	3 hours
Transfer Time	6 ms
Features	Maintenance free, sealed, leak-proof
Networking	
Remote Management Interface	RS-232, USB
Expansion / Connectivity	
Interfaces	1 x management (RS-232) 1 x USB 1 x EPO (emergency power off)
Expansion Slots	1 (total) / 1 (free) x SmartSlot
Miscellaneous	
Cables Included	USB cable - external
Features	Audible alarm, emergency power off, LCD display, Automatic Voltage Regulation (AVR), cold-start function, automatic self-test, predictive failure notification, hot-swappable batteries, energy metre
Compliant Standards	CSA, UL 1778, VDE, IEC 62040-2, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1
Software / System Requirements	
Software Included	APC PowerChute Business Edition
Manufacturer Warranty	
Service & Support	Limited warranty - replace or repair - 3 years Limited warranty - batteries - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%



Sound Emission	45 dBA
Dimensions & Weight	
Width	17.1 cm
Depth	43.9 cm
Height	21.9 cm
Weight	24.09 kg
Dimensions & Weight (Shipping)	
Shipping Width	32.8 cm
Shipping Depth	59.5 cm
Shipping Height	37.6 cm
Shipping Weight	27.23 kg

Technical data © CNET Content Solutions. Subject to technical modifications and errors.