

MPN: 6FUTP-20BL

CAT6 F/UTP CU LSZH Ethernet Cable Blue 20m

The CAT6 F/UTP CU ethernet cables are produced with 99.9% pure copper strands and an AWG of 26 to ensure the absolute best performance. The outer jacket of the cable is made from LSZH (Low Smoke Zero Halogen) ensuring low amounts of smoke, toxic fumes, and no acid gasses in case of a fire. The cable is also wrapped in a foil screen that enables protection against electromagnetic interference (EMI), and reinforced with strain relief for increased durability and a snagless latch protection allowing secure installation. Plated with 50"U gold, the connector provides more durability and a higher quality transmission rate. A 50"U gold connector can deliver up to 4x more throughput than a standard metal connector. 50"U is the thickest available and most optimal gold plating.

All CAT6 F/UTP CU ethernet cables support PoE+. Supporting a variety of cable standards, lengths and shieldings, is your one stop shop for ethernet cables ensuring that you are always able to find a cable that best suits your network requirements.



Caractéristiques

| | | | |
|-------------------------------------|------------------------------------------|----------------------------------------|-------------|
| Caractéristiques | Blindage du câble | F/UTP (FTP) | |
| | Câble standard | Cat6 | |
| | Connecteur 1 | RJ45 | |
| | Connecteur 2 | RJ45 | |
| | Contacts du connecteur de placage | Or | |
| | Couleur du produit | Bleu | |
| | Genre de connecteur 1 | Mâle | |
| | Genre de connecteur 2 | Mâle | |
| | Longueur de câble | 20 m | |
| | Matériau conducteur | Cuivre | |
| | Matériau du manteau | LSZH (Low smoke zero halogen) | |
| | Plug and Play | Oui | |
| | Standards réseau | IEEE 802.3at | |
| | Taille des fils AWG | 26 | |
| | Taux de transfert de données | 1000 Mbit/s | |
| | Technologie de câblage | 10/100/1000Base-T(X) | |
| | Type de conducteur | Gainé | |
| | Certificat | Certification | REACH |
| | Conditions environnementales | Température d'opération | -10 - 60 °C |
| | | Température hors fonctionnement | -15 - 60 °C |
| Détails techniques | Certificats de conformité | RoHS | |
| | Certificats de durabilité | RoHS | |
| Informations sur l'emballage | Manuel d'utilisation | Non | |
| | Quantité | 1 pièce(s) | |

Poids et dimensions

| | |
|---------------------------|--------|
| Diamètre extérieur | 5,8 mm |
|---------------------------|--------|

Vendor information

| | |
|-------------------|--------------|
| Brand Name | ProXtend |
| Warranty | 30 Année (s) |

Autres photos

